



STAUFF  
Filtri  
Return-line filters




 HYDRAULIC  
COMPONENTS  
& FLUID CONTAMINATION  
CONTROL



All trademarks belong to their respective owners; third party trademarks, product names, trade names, corporate names and company names mentioned may be trademarks of their respective owners or registered trademarks of other companies and are used for instructional purposes and for the benefit of the owner, without any end of Copyright infringement in force.

Tutti i marchi riportati appartengono ai legittimi proprietari; marchi di terzi, nomi di prodotti, nomi commerciali, nomi corporativi e società citati possono essere di proprietà dei rispettivi titolari o registrati da altre società e sono stati utilizzati a puro scopo esplicativo e a beneficio del possessore, senza alcun fine di violazione dei diritti di Copyright vigenti.



**Overview Return-Line Filters** 68

RF / RFA / RFB / RFS / RFS-D / RTF / RTF-N



**Return-Line Filters** **RF** 69 - 76  
 Max. 16 bar / 232 PSI  
 Max. 500 l/min / 130 US GPM

Technical Data / Dimensions 70 - 71

Order Code - Return-Line Filter 72

Order Code - Filter Elements 72

**Options - Clogging Indicators** 73 - 74

**Flow Characteristics** 75 - 76



**Return-Line Filters** **RFA** 77 - 83  
 Max. 25 bar / 365 PSI  
 Max. 110 l/min / 30 US GPM

Technical Data / Dimensions 78 - 79

Order Code - Return-Line Filter 80

Order Code - Filter Elements 80

**Options - Clogging Indicators** 81 - 82

**Flow Characteristics** 83

**Checklist for the selection of filter housings** 84



**Return-Line Filters** **RFB** 85 - 91  
 Max. 10 bar / 145 PSI  
 Max. 185 l/min / 52 US GPM







Technical Data / Dimensions 86 - 87

Order Code - Return-Line Filter 88

Order Code - Filter Elements / Air Filter Elements 88

**Options - Clogging Indicators** 89 - 90

**Flow Characteristics** 91

	<b>Checklist for the selection of filter housings</b>	<b>92</b>			
	<b>Return-Line Filters</b> Max. 25 bar / 365 PSI Max. 1135 l/min / 300 US GPM	<b>RFS / RFS-D</b>	<b>93 - 102</b>		<b>Return-Line Filters</b> Max. 6,9 bar / 100 psi Max. 379 l/min / 100 US GPM
	Technical Data / Dimensions		<b>94 - 97</b>		Technical Data / Dimensions
	Order Code - Return-Line Filter		<b>98</b>		Order Code - Return-Line Filter
	Order Code - Filter Elements		<b>98</b>		Order Code - Filter Elements
	<b>Options - Clogging Indicators</b>		<b>99 - 100</b>		
	<b>Flow Characteristics</b>		<b>101 - 102</b>		
	<b>Return-Line Filters</b> Max. 6,9 bar / 100 PSI Max. 95 l/min / 25 US GPM	<b>RTF-10/15/25</b>	<b>103 - 106</b>		<b>Return-Line Filters</b> Max. 10 bar / 145 psi Max. 500 l/min / 132 GPM
	Technical Data / Dimensions		<b>104 - 105</b>		Technical Data / Dimensions
	Order Code - Return-Line Filter		<b>106</b>		Order Code - Return-Line Filter
	Order Code - Filter Elements		<b>106</b>		Order Code - Filter Elements
					<b>Flow Characteristics</b>
					RTF
					<b>Options - Clogging Indicators</b>
	<b>Return-Line Filters</b> Max. 6,9 bar / 100 PSI Max. 115 l/min / 30 US GPM	<b>RTF-20</b>	<b>107 - 110</b>		
	Technical Data / Dimensions		<b>108 - 109</b>		
	Order Code - Return-Line Filter		<b>110</b>		
	Order Code - Filter Elements / Air Filter Elements		<b>110</b>		
	<b>Return-Line Filters</b> Max. 6,9 bar / 100 psi Max. 378 l/min / 100 US GPM	<b>RTF-40</b>	<b>111 - 114</b>		
	Technical Data / Dimensions		<b>112 - 113</b>		
	Order Code - Return-Line Filter		<b>114</b>		
	Order Code - Filter Elements		<b>114</b>		

**D**


## Description

STAUFF Return-Line Filters were designed as filters for tank-top mounting, tank-inside mounting or inline mounting. They filter the hydraulic oil before it flows back into the reservoir. This ensures that contamination arising in the components does not get into the tank. Return-Line filters maintain the targeted purity class like Pressure Filters. However, because of their arrangement, they do not fulfil the additional function of a protection filter. In contrast to a Pressure Filter, it only has to withstand low pressure levels.

The practical design of STAUFF Return-Line Filters enables quick assembly as well as easy exchange of the filter elements.

### Media Compatibility

- Mineral oils, others on request

### Options and Accessories

#### Valves

- Bypass valve integrated in the filter element (except STAUFF Return-Line Filter RTF)

#### Clogging Indicators

- On request with visual clogging indicator or electrical clogging switch
- Others on request




#### Type RF

- Filter bowl with option of thread connection (e.g. STAUFF Diffuser SRV) or leakage oil connection
- Operating pressure: max. 16 bar / 232 PSI
- Nominal flow rate: max. 500 l/min / 130 US GPM
- Materials: Filter head: Aluminium, Filter bowl: PA
- Connections: BSP, NPT, SAE thread or SAE flange (ISO 6162-1)



#### Type RFA

- Filter bowl with option of thread connection (e.g. STAUFF Diffuser SRV) or leakage oil connection
- Operating pressure: max. 25 bar / 365 PSI
- Nominal flow rate: max. 110 l/min / 30 US GPM
- Materials: Filter housing: Aluminium
- Connection: SAE thread



#### Type RFB

- Low weight and compact design
- Filter bowl with option of thread connection
- Filter head with option of integrated air filter
- Operating pressure: max. 10 bar / 145 PSI
- Nominal flow rate: max. 185 l/min / 52 US GPM
- Materials: Filter head: Aluminium, Filter bowl: PA
- Connections: BSP, NPT, SAE thread



#### Type RFS and RFS-D

- Robust design, suitable for high flow rates
- Filter bowl with option of BSP or SAE flange
- Operating pressure: max. 25 bar / 365 PSI
- Nominal flow rate: max. 1135 l/min / 300 US GPM
- Materials: Filter head and bowl: Steel
- Connections: BSP or SAE flange (ISO 6162-1)



#### Type RTF

- Filter bowl is designed to return the oil beneath the surface thus preventing entrainment of air
- Filter head with option of integrated air filter
- Operating pressure: max. 10 bar / 49 PSI
- Nominal flow rate: max. 380 l/min / 100 US GPM
- Materials: Filter head: Aluminium, Filter bowl: PA or Steel
- Connection: BSP or NPT, others on request




#### Type RTF-N

- Return-Line insert filter
- Custom reservoir design with an in-tank filtering system
- Magnetic pre-filtration
- Operating pressure: max. 10 bar / 145 PSI
- Nominal flow rate: max. 500 l/min / 132 US GPM
- Materials: Flange plate: Aluminium, Magnet rod / Bypass / Diffuser: Steel



## Return-Line Filters ■ Type RF



D

**Product Description**

STAUFF RF Return-Line Filters are designed as tank top filters. They are mounted directly on the tank top and when 100% of the system's oil is filtered they provide the optimum removal of contaminant from the system. This provides the pump with clean oil thus reducing contaminant generated wear. The filter bowl is designed to return the oil beneath the surface thus preventing the entrainment of air by the returning oil. A high efficiency of contaminant removal is assured by using STAUFF RE Replacement Filter Elements. The high dirt-hold capacity of STAUFF Elements ensures a long service life and as a result reduced maintenance costs.

**Technical Data**
**Construction**

- Tank Top flange mounting

**Materials**

- Filter head: Aluminium
- Filter bowl: Glass Fibre reinforced Polyamide
- Sealings: NBR (Buna-N®)  
FKM (Viton®)  
EPDM (Ethylene-Propylene-Diene-Monomer-Rubber)  
Other sealing materials on request

**Port Connections**

- BSP
- NPT
- SAE O-ring thread
- SAE flange 3000 PSI

**Operating Pressure**

- Max. 16 bar / 232 PSI

**Temperature Range**

- -10 °C ... +100 °C / +14 °F ... +212 °F

**Filter Elements**

- Specifications see page 72

**Media Compatibility**

- Mineral oils, other fluids on request

**Options and Accessories**
**Valve**

- Bypass valve (integrated in the filter element): Opening pressure 3 bar ± 0,3 bar / 43.5 PSI ± 4.35 PSI  
Other settings available on request


**Clogging Indicators**

- For clogging indicator types please see page 73



Return-Line Filters ▪ Type RF

D



## Return-Line Filters ■ Type RF

Thread Connection G	Filter Size RF					
	014	030	045	070	090	130
BSP	3/4	1	1-1/4	1-1/2	2	2
NPT	3/4	1	1-1/4	1-1/2	2	2
SAE O-ring Thread	1-1/16-12	1-5/16-12	1-5/8-12	1-7/8-12	1-7/8-12	1-7/8-12
SAE Flange 3000 PSI	-	-	-	-	2	2

Dimensions (mm/in)	Filter Size RF					
	014	030	045	070	090	130
b1	89	89	120	120	150	150
	3.50	3.50	4.72	4.72	5.91	5.91
b2	80	80	110	110	135	135
	3.15	3.15	4.33	4.33	5.31	5.31
b3	-	-	-	-	88	88
	-	-	-	-	3.47	3.47
b4	-	-	-	-	102	102
	-	-	-	-	4.02	4.02
b5	-	-	-	-	42,9	42,9
	-	-	-	-	1.69	1.69
b6	-	-	-	-	77,8	77,8
	-	-	-	-	3.06	3.06
d1	73	73	100	100	126	126
	2.87	2.87	3.94	3.94	4.96	4.96
d2	57,5	57,5	84	84	112,5	112,5
	2.26	2.26	3.31	3.31	4.43	4.43
d3	36	36	48	48	54,5	54,5
	1.42	1.42	1.89	1.89	2.15	2.15
d4	17	17	28	28	37,5	37,5
	.67	.67	1.1	1.1	1.48	1.48
d5	100	100	135	135	170	170
	3.94	3.94	5.31	5.31	6.69	6.69
d6	78	78	105	105	131	131
	3.07	3.07	4.13	4.13	5.16	5.16
h1	33	33	41	41	47	47
	1.30	1.30	1.61	1.61	1.85	1.85
h2	66	66	86	86	98	98
	2.60	2.60	3.39	3.39	3.86	3.86
h3	91,5	159,5	119	180	172,5	252,5
	3.60	6.28	4.69	7.09	6.79	9.94
h4	157,5	225,5	206	267	273,5	353,5
	6.20	8.88	8.11	10.51	10.77	13.91
h5	23,5	23,5	24	24	27	27
	.93	.93	.95	.95	1.06	1.06
h6	140	210	180	240	235	315
	5.51	8.27	7.09	9.45	9.25	12.40
I1	48	48	66	66	85	85
	1.89	1.89	2.60	2.60	3.35	3.35
G2	G1 or 1 NPT	G1 or 1 NPT	G1-1/4 or 1-1/4 NPT	G1-1/4 or 1-1/4 NPT	G1-1/2 or 1-1/2 NPT	G1-1/2 or 1-1/2 NPT
G3	-	-	-	-	M12x15	M12x15
G4	M6 or 1/4-20 UNC	M6 or 1/4-20 UNC	M8 or 5/16-18 UNC	M8 or 5/16-18 UNC	M10 or 3/8-16 UNC	M10 or 3/8-16 UNC
Hex	36	36	50	50	55	55
	1.42	1.42	1.97	1.97	2.16	2.16





## Return-Line Filter Housings / Complete Filters ■ Type RF

RF - 070 - G - 10 - B - G24 - G42NO - D - O - L1 / X

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

## ① Type

Return-Line Filter **RF**

## ② Group

Flow	Size
60 l/min / 14 US GPM	<b>014</b>
110 l/min / 30 US GPM	<b>030</b>
160 l/min / 45 US GPM	<b>045</b>
240 l/min / 70 US GPM	<b>070</b>
330 l/min / 90 US GPM	<b>090</b>
500 l/min / 130 US GPM	<b>130</b>

Note: Exact flow will depend on the selected filter element. For technical data please see pages 75 / 76.

## ③ Filter Material

Material	max. $\Delta p^*$ collapse	Micron ratings available	Code
Without filter element	-	-	<b>O</b>
Inorg. glass fibre	25 bar / 363 PSI	3, 5, 10, 20	<b>G</b>
Stainless fibre	30 bar / 435 PSI		<b>A</b>
Filter paper	10 bar / 145 PSI	10, 20	<b>N</b>
Stainless mesh	30 bar / 435 PSI	25, 50, 100, 200	<b>S</b>

Note: \*Collapse/burst resistance as per ISO 2941. Other materials on request.

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
20 $\mu$ m	<b>20</b>
25 $\mu$ m	<b>25</b>
50 $\mu$ m	<b>50</b>
100 $\mu$ m	<b>100</b>
200 $\mu$ m	<b>200</b>

Note: Other micron ratings on request.

## ⑤ Sealing Materials

NBR (Buna®) **B**  
 FKM (Viton®) **V**  
 EPDM **E**

Note: Other sealing materials on request

## ⑥ Connection Style

Connection Style	Thread Style	Group 014	Code	Group 030	Code	Group 045	Code	Group 070	Code	Group 090	Code	Group 130	Code
BSP	-	3/4	<b>G12</b>	1	<b>G16</b>	1-1/4	<b>G20</b>	1-1/2	<b>G24</b>	2	<b>G32</b>	2	<b>G32</b>
BSP	-	1/2	G08	1/2	G08	1-1/2	G24	1-1/4	G20	1-1/4	G20	1-1/4	G20
BSP	-	1	G16	3/4	G12	-	-	-	-	1-1/2	G24	1-1/2	G24
NPT	-	3/4	<b>N12</b>	1	<b>N16</b>	1-1/4	<b>N20</b>	1-1/2	<b>N24</b>	2	<b>N32</b>	2	<b>N32</b>
NPT	-	1	N16	3/4	N12	1-1/2	N24	1-1/4	N20	1-1/2	N24	1-1/2	N24
SAE O-ring Thread	-	1-1/16	<b>U12</b>	1-5/16	<b>U16</b>	1-5/8	<b>U20</b>	1-7/8	<b>U24</b>	1-7/8	<b>U24</b>	1-7/8	<b>U24</b>
SAE O-ring Thread	-	1-5/16	U16	1-1/16	U12	1-7/8	U24	1-5/8	U20	1-5/8	U20	1-5/8	U20
SAE Flange 3000 PSI	metric	-	-	-	-	-	-	-	-	2	<b>C332M</b>	2	<b>C332M</b>
SAE Flange 3000 PSI	UNC	-	-	-	-	-	-	-	-	2	<b>C332U</b>	2	<b>C332U</b>

Note: Bold types identify preferred connection styles.

## ⑦ Clogging Indicator

Without Clogging Indicator **O**  
 Visual Clogging Indicator **V**  
 Electrical Clogging Switch 42 V, NO **G42NO**  
 Electrical Clogging Switch 42 V, NC **G42NC**  
 Electrical Clogging Switch 110 V ... 230 V, two-way contact (only for Code W) **G230**

## ⑧ Option Clogging Indicator G42NO, G42NC and G230

Plug connector **O**  
 M12 x 1,5 **M12**  
 AMP plug **A**  
 Deutsch plug **D**  
 Rubber boot **S**  
 90 degree Polyamide cap (only for Code G230) **W**

## ⑨ Outlet Style

Size	Connection thread	Code
all	Without thread (Standard outlet)	<b>O</b>
014 / 030	1" BSP / 1" NPT	<b>G16 / N16</b>
045 / 070	1 1/4 BSP / 1 1/4 NPT	<b>G20 / N20</b>
90 / 130	1 1/2 BSP / 1 1/2 NPT	<b>G24 / N24</b>

## ⑩ Additional Features

	Position*	
Without leakage oil connection	-	<b>none</b>
Leakage oil connection	1 2	<b>L</b>

Note: \*Position of the leakage oil connection see page 70.

Without any code: assembly in the middle of the filter cover.

## ⑪ Design Code

Only for information **X**

## Filter Elements ■ Type RE

RE - 014 - G - 10 - B / X

① ② ③ ④ ⑤ ⑥

## ① Type

Filter Element Series **RE**

## ② Group

According to filter housing

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Inorg. glass fibre	25 bar / 363 PSI	3, 5, 10, 20	<b>G</b>
Stainless fibre	30 bar / 435 PSI		<b>A</b>
Filter paper	10 bar / 145 PSI	10, 20	<b>N</b>
Stainless mesh	30 bar / 435 PSI	25, 50, 100, 200	<b>S</b>

Note: \*Collapse/burst resistance as per ISO 2941. Other materials on request.

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
20 $\mu$ m	<b>20</b>
25 $\mu$ m	<b>25</b>
50 $\mu$ m	<b>50</b>
100 $\mu$ m	<b>100</b>
200 $\mu$ m	<b>200</b>

Note: Other micron ratings on request.

## ⑤ Sealing Materials

NBR (Buna®) **B**  
 FKM (Viton®) **V**  
 EPDM **E**

Note: Other sealing materials on request.

## ⑥ Design Code

Only for information **X**

## Return-Line Filters ■ Type RF

## Electrical Clogging Switch

The switch is used where an electrical signal is needed to indicate when the element needs to be changed. The switch can turn on a light, or shut the machine down, or any further function controlled by an electric signal. The switching pressure is 2,5 bar / 36.25 PSI and this allows the element to be changed before the bypass setting of 3 bar / 43.5 PSI is reached.

Standard type with plug connector and rubber cap. Available with DEUTSCH DT04-2P plug (industrial standard), AMP Junior Timer plug (industrial standard) and five-pin circular connector M12, A-coded, according to IEC 61076-2-101.

## Technical Data

	Limit-Switch G42NO+NC	Limit-Switch G230
Switching Capacity	100 VA	1000 VA
Voltage	10...42 VAC	10...250 VAC
Current		10mA...4A
Switching Accuracy		± 0,5 bar at room temp. and new state
Switching Frequency		200/min
max. Pressure Ramp Rate		≤ 1 bar/ms
Degree of Protection		IP65 (plug type S and W), IP67 (plug type M12, A, D)
Temperature Range	-30°C ... +100°C	-40°C ... +100°C

## Order Code

**Limit-Switch - G42NO - S - M10 - B2.5**

①

②

③

④

⑤

## ① Type

Limit-Switch

## ② Connector Type

Electrical Clogging Switch 42 V, NO	<b>G42NO</b>
Electrical Clogging Switch 42 V, NC	<b>G42NC</b>
Electrical Clogging Switch 110 V ... 230 V, two-way contact (only for Plug Type W)	<b>G230</b>

## ③ Plug Type

M12 Five-Pin Connector according to IEC 61076-2-101	<b>M12</b>
AMP-Junior-Timer Plug	<b>A</b>
DEUTSCH Plug DT04-2P	<b>D</b>
Rubber boot	<b>S</b>
90 degree Polyamide cap (only for Connector Type G230)	<b>W</b>


## ④ Thread Type

 M10 x 1 **M10**

## ⑤ Pressure Setting

 2,5 bar / 36.3 PSI **B2.5**

## Dimensions Plug Type



Note: The customer / user carries the responsibility for the electrical connection.



## Return-Line Filters - Type RF

### Visual Clogging Indicator

The gauge visually displays the degree of contamination of the element.  
The colored segments allow quick visual checking.

green	0 ... 2,5 bar / 0 ... 36.25 PSI	Element has service life left
yellow	2,5 ... 3,0 bar / 36.25 ... 43.5 PSI	Element is contaminated and should be changed
red	>3,0 bar / >43.5 PSI	Bypass valve open, unfiltered oil passing to tank


### Order Codes

**SPG-C-040-00004-02-P-M10-402922**



#### ① Type

Visual Clogging Indicator **SPG-C-040-00004-02-P-M10-402922**



### Filter Bowl with Threaded Connection

Under some circumstances such as a tall reservoir or one with oil levels which vary greatly during operation, it is necessary to extend the filter bowl so that the returning oil returns beneath the surface and does not entrain air in the process. The optional bowl with a female thread allows an extension to be fitted quite simply.




### Leakage Oil Connection

Seal or case drain lines can be connected to the filter through either of the clogging indicator ports providing that the leakage oil can accept a pressure of 3 bar / 43.5 PSI. It ensures that no unfiltered oil can return to the reservoir.

### Filter Bowl with Threaded Connection and Diffuser












Diffusers mounted to the filter bowl minimise foaming and reduce noise of high Return-Line flows. For further details on STAUFF Diffusers please refer to the Catalogue No. 10 - Hydraulic Accessories.  
Attention: Connection pipe not included in scope of delivery!

Size SRV	for Return-Line Filter Size	Dimensions (mm/in)		Thread G	Hex
		øD	L		
SRV-114-G16	RF-014/030	60	139	G1	46
SRV-114-N16		2.36	5.47	1 NPT	1.81
SRV-200-G20	RF-045/070	82	139	G1-1/4	60
SRV-200-N20		3.23	5.47	1-1/4 NPT	2.36
SRV-227-G24	RF-090/130	82	200	G1-1/2	60
SRV-227-N24		3.23	7.87	1-1/2 NPT	2.36



## Return-Line Filters • Type RF Flow Characteristics







The following characteristics are valid for mineral oils with a density of 0,85 kg/dm<sup>3</sup> and the kinematic viscosity of 30 mm<sup>2</sup>/s (30cSt). The characteristics have been determined in accordance to ISO 3968. Multipass filter ratings have been obtained in accordance to ISO 16889. The housing pressure drop is directly proportional to the oil density. Contact STAUFF for details.

**Housings RF-014/030**

**Housings RF-045/070**

**Housings RF-090/130**

**Filter Elements RE-014-A**

**Filter Elements RE-030-A**

**Filter Elements RE-045-A**

**Filter Elements RE-070-A**

**Filter Elements RE-090-A**

**Filter Elements RE-130-A**

**Filter Elements RE-...S**

**Filter Elements RE-...N**


### Return-Line Filters - Type RF Flow Characteristics

The following characteristics are valid for mineral oils with a density of 0,85 kg/dm<sup>3</sup> and the kinematic viscosity of 30 mm<sup>2</sup>/s (30cSt). The characteristics have been determined in accordance to ISO 3968. Multipass filter ratings have been obtained in accordance to ISO 16889. The housing pressure drop is directly proportional to the oil density. Contact STAUFF for details.

D



## Return-Line Filters ■ Type RFA



D

**Product Description**

STAUFF RFA Return-Line Filters are a one piece design and can be used as a tank top or an in-line filter. They are mounted in the Return-Line and if 100% of the system oil is filtered, provide the optimum removal of contaminant for the systems. This provides the pump with clean oil, thus reducing contaminant generated wear. A high efficiency of contaminant removal is assured by using STAUFF RE Replacement Filter Elements. The high dirt-hold capacity of STAUFF Elements ensures a long service life and as a result reduced maintenance costs. Furthermore, this housing also offers the possibility of pipeline mounting.

**Technical Data**
**Construction**

- Tank Top or in-line mounting

**Materials**

- Filter housing: Aluminium
- Sealings: NBR (Buna-N®)  
FKM (Viton®)  
EPDM (Ethylene Propylene Diene Monomer Rubber)  
Other sealing materials on request

**Port Connections**

- SAE O-ring thread
- BSP

**Operating Pressure**

- Max. 25 bar / 365 PSI

**Temperature Range**

- -10 °C ... +100 °C / +14 °F ... +212 °F

**Filter Elements**

- Specifications see page 80

**Media Compatibility**

- Mineral oils, other fluids on request

**Options and Accessories**
**Valve**

- Bypass valve (integrated in the filter element)      Opening pressure 3 bar ± 0,3 bar / 43.5 PSI ± 4.35 PSI  
Other settings available on request




**Clogging Indicators**

- For clogging indicator types please see page 81



Return-Line Filters ▪ Type RFA

D



Mounting Detail

\* recommended space for element change



## Return-Line Filters ▪ Type RFA

Thread Connection G	Filter Size RFA-030
SAE O-ring Thread U12	1-1/16-12
SAE O-ring Thread U08	3/4-16
BSP G08	1/2
BSP G12	3/4

Dimensions (mm/in)	Filter Size RFA-030
h1	29,5
	1.16
h2	62,5
	2.46
h3	163,5
	6.44
h4	233,5
	9.19
h5	28
	1.10
h6	210
	8.27
b1	89
	3.50
b2	80
	3.15
d1	70
	2.76
d2	44,5
	1.75
d3	100
	3.94
d4	74
	2.91
l1	54
	2.16
G2	M6 or 1/4 UNC

D





## Return-Line Filter Housings / Complete Filters ■ Type RFA

**RFA** - **030** - **G** - **10** - **B** - **G08** - **G42NO** - **D** - **O** - **L1** / **X**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

## ① Type

Return-Line Filter **RFA**

## ② Group

**Flow** **Size**  
110 l/min / 30 US GPM **030**  
Note: Exact flow will depend on the selected filter element.  
For technical data please see page 83.

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Without filter element	-	-	<b>O</b>
Inorg. glass fibre	25 bar / 363 PSI	3, 5, 10, 20	<b>G</b>
Stainless fibre	30 bar / 435 PSI		<b>A</b>
Filter paper	10 bar / 145 PSI	10, 20	<b>N</b>
Stainless mesh	30 bar / 435 PSI	25, 50, 100, 200	<b>B, S</b>

Note: \*Collapse/burst resistance as per ISO 2941.  
Other materials on request.

## ④ Micron Rating

3 $\mu\text{m}$	<b>03</b>
5 $\mu\text{m}$	<b>05</b>
10 $\mu\text{m}$	<b>10</b>
20 $\mu\text{m}$	<b>20</b>
25 $\mu\text{m}$	<b>25</b>
50 $\mu\text{m}$	<b>50</b>
100 $\mu\text{m}$	<b>100</b>
200 $\mu\text{m}$	<b>200</b>

Note: Other micron ratings on request.

## ⑤ Sealing Material

NBR (Buna®) **B**  
FKM (Viton®) **V**  
EPDM **E**  
Note: Other sealing materials on request

## ⑥ Connection Style

Connection Style	Thread	Code
SAE-O-ring Thread	1-1/16-12	<b>U12</b>
SAE-O-ring Thread	3/4-16	<b>U08</b>
BSP	1/2	<b>G08</b>
BSP	3/4	<b>G12</b>

## ⑦ Clogging Indicator

Without Clogging Indicator **O**  
Visual Clogging Indicator **V**  
Electrical Clogging Switch 42 V, NO **G42NO**  
Electrical Clogging Switch 42 V, NC **G42NC**  
Electrical Clogging Switch 230 V, two-way contact (only for Code W) **G230**

## ⑧ Option Clogging Indicator G42NO, G42NC and G230

Plug connector **O**  
M12 x 1,5 **M12**  
AMP plug **A**  
Deutsch plug **D**  
Rubber boot **S**  
90 degree Polyamide cap (only for Code G230) **W**

## ⑨ Outlet Style

Connection Style	Thread	Code
	Without thread (Standard outlet)	<b>O</b>
SAE-O-Ring Thread	1-1/16-12	<b>U12</b>
SAE-O-Ring Thread	3/4-16	<b>U08</b>
BSP	1/2	<b>G08</b>
BSP	3/4	<b>G12</b>

## ⑩ Additional Features

	Position*		
Without leakage oil connection	-		<b>none</b>
Leakage oil connection	1	2	<b>L1</b>

Note: \*Position of the leakage oil connection see page 78.

Without any code: assembly in the middle of the filter cover.

## ⑪ Design Code

Only for information **X**

## Filter Elements ■ Type RE

**RE** - **030** - **G** - **10** - **B** / **X**

① ② ③ ④ ⑤ ⑥

## ① Type

Filter Element Series **RE**

## ② Group

According to filter housing

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Inorg. glass fibre	25 bar / 363 PSI	3, 5, 10, 20	<b>G</b>
Stainless fibre	30 bar / 435 PSI		<b>A</b>
Filter paper	10 bar / 145 PSI	10, 20	<b>N</b>
Stainless mesh	30 bar / 435 PSI	25, 50, 100, 200	<b>B, S</b>

Note: \*Collapse/burst resistance as per ISO 2941. Other materials on request.

## ④ Micron Rating

3 $\mu\text{m}$	<b>03</b>
5 $\mu\text{m}$	<b>05</b>
10 $\mu\text{m}$	<b>10</b>
20 $\mu\text{m}$	<b>20</b>
25 $\mu\text{m}$	<b>25</b>
50 $\mu\text{m}$	<b>50</b>
100 $\mu\text{m}$	<b>100</b>
200 $\mu\text{m}$	<b>200</b>

Note: Other micron ratings on request.

## ⑤ Sealing Materials

NBR (Buna®) **B**  
FKM (Viton®) **V**  
EPDM **E**  
Note: Other sealing materials on request.

## ⑥ Design Code

Only for information **X**

## Return-Line Filters ■ Type RFA

## Electrical Clogging Switch

The switch is used where an electrical signal is needed to indicate when the element needs to be changed. The switch can turn on a light, or shut the machine down, or any further function controlled by an electric signal. The switching pressure is 2,5 bar / 36.25 PSI and this allows the element to be changed before the bypass setting of 3 bar / 43.5 PSI is reached.

Standard type with plug connector and rubber cap. Available with DEUTSCH DT04-2P plug (industrial standard), AMP Junior Timer plug (industrial standard) and five-pin circular connector M12, A-coded, according to IEC 61076-2-101.

## Technical Data

	Limit-Switch G42NO+NC	Limit-Switch G230
Switching Capacity	100 VA	1000 VA
Voltage	10...42 VAC	10...250 VAC
Current		10mA...4A
Switching Accuracy		± 0,5 bar at room temp. and new state
Switching Frequency		200/min
max. Pressure Ramp Rate		≤ 1 bar/ms
Degree of Protection	IP65 (plug type S and W), IP67 (plug type M12, A, D)	
Temperature Range	-30°C ... +100°C	-40°C ... +100°C

## Order Code

**Limit-Switch - G42NO - S - M10 - B2.5**

①

②

③

④

⑤

## ① Type

Limit-Switch

## ② Connector Type

Electrical Clogging Switch 42 V, NO	<b>G42NO</b>
Electrical Clogging Switch 42 V, NC	<b>G42NC</b>
Electrical Clogging Switch 110 V ... 230 V, two-way contact (only for Plug Type W)	<b>G230</b>

## ③ Plug Type

M12 Five-Pin Connector according to IEC 61076-2-101	<b>M12</b>
AMP-Junior-Timer Plug	<b>A</b>
DEUTSCH Plug DT04-2P	<b>D</b>
Rubber boot	<b>S</b>
90 degree Polyamide cap (only for Connector Type G230)	<b>W</b>


## ④ Thread Type

 M10 x 1 **M10**

## ⑤ Pressure Setting

 2,5 bar / 36.3 PSI **B2.5**

## Dimensions Plug Type



Note: The customer / user carries the responsibility for the electrical connection.

Dimensional drawings: All dimensions in mm/in.



## Return-Line Filters - Type RFA

### Visual Clogging Indicator

The gauge visually displays the degree of contamination of the element.  
The colored segments allow quick visual checking.

green	0 ... 2,5 bar / 0 ... 36.25 PSI	Element has service life left
yellow	2,5 ... 3,0 bar / 36.25 ... 43.5 PSI	Element is contaminated and should be changed
red	>3,0 bar / >43.5 PSI	Bypass valve open, unfiltered oil passing to tank


### Order Codes

**SPG-C-040-00004-02-P-M10-402922**




### 1 Type

Visual Clogging Indicator **SPG-C-040-00004-02-P-M10-402922**




### Filter Bowl with Threaded Connection

Under some circumstances such as a tall reservoir or one with oil levels which vary greatly during operation, it is necessary to extend the filter bowl so that the returning oil returns beneath the surface and does not entrain air in the process. The optional bowl with a female thread allows an extension to be fitted quite simply. The one piece design also allows for inline applications.



### Leakage Oil Connection


Seal or case drain lines can be connected to the filter through either of the clogging indicator ports providing that the leakage oil can accept a pressure of 3 bar / 43.5 PSI. It ensures that no unfiltered oil can return to the reservoir.



### Filter Bowl with Threaded Connection and Diffuser





Diffusers mounted to the filter bowl minimise foaming and reduce noise of high Return-Line flows. For further details on STAUFF Diffusers please refer to the Catalogue No. 10 - Hydraulic Accessories.  
Attention: Connection pipe not included in scope of delivery!

Size SRV	for Return-Line Filter Size	Dimensions (mm/in)		Thread G	Hex
		øD	L		
SRV-050-G12	RFA-030	62	109	G3/4	36
SRV-050-N12		2.44	4.29	3/4 NPT	1.42



## Return-Line Filters ■ Type RFA Flow Characteristics

The following characteristics are valid for mineral oils with a density of 0,85 kg/dm<sup>3</sup> and the kinematic viscosity of 30 mm<sup>2</sup>/s (30cSt). The characteristics have been determined in accordance to ISO 3968. Multipass filter ratings have been obtained in accordance to ISO 16889. The housing pressure drop is directly proportional to the oil density. Contact STAUFF for details.



### Checklist for the selection of filter housings

Please use the following Checklist as a guideline when preparing an enquiry for the selection of filter housings. Scan or copy the page from the catalogue, print and com-

plete it with as much information as possible, before sending it by email or fax to the closest STAUFF branch office. If possible, please also let us know the quantities required,

and if the enquiry is for a one-time or recurring demand. We look forward to hearing from you, and are always available for consultation, when required.

D

<b>Information on the fluid in use</b>					
<b>Type of fluid</b>	<input type="text"/>	Brand	<input type="text"/>	ISO designation	
<b>Fluid viscosity</b>	<input type="text"/>	<input type="checkbox"/>	mm <sup>2</sup> /sec	<input type="checkbox"/>	cSt
<b>Fluid temperature</b>	<input type="text"/>	°C	<input type="checkbox"/>	°F	<input type="text"/>
			<input type="checkbox"/>	In cold condition	<input type="text"/>
					<input type="checkbox"/>
					In warm condition
<b>Information on the filter housing</b>					
<b>Position in the hydraulic system</b>	<input type="checkbox"/>	Suction line	<input type="checkbox"/>	Pressure line	<input type="checkbox"/>
					Return line
<b>Operating pressure</b>	<input type="text"/>	<input type="checkbox"/>	bar	<input type="checkbox"/>	PSI
<b>Nominal flow</b>	<input type="text"/>	<input type="checkbox"/>	l/min	<input type="checkbox"/>	US GPM
<b>Valve</b>	<input type="checkbox"/>	No, not required			
	<input type="checkbox"/>	Yes, the following type:			
		<input type="checkbox"/>	Bypass valve	<input type="checkbox"/>	Non-return valve
				<input type="checkbox"/>	Reverse flow valve
				<input type="checkbox"/>	Multi-function valve
<b>Clogging indicator</b>	<input type="checkbox"/>	No, not required			
	<input type="checkbox"/>	Yes, the following type:			
		<input type="checkbox"/>	Visual	<input type="checkbox"/>	Electrical
				<input type="checkbox"/>	Visual-electrical
<b>Connection type and size</b>	<input type="text"/>				
<b>Sealing material</b>	<input type="checkbox"/>	NBR (Buna®)	<input type="checkbox"/>	FKM (Viton®)	<input type="text"/>
					Other
<b>Information on the filter element</b>					
<b>Filter media</b>	<input type="checkbox"/>	Inorganic Glass Fibre	<input type="checkbox"/>	Polyester Fibre	<input type="checkbox"/>
			<input type="checkbox"/>	Cellulose Fibre	<input type="checkbox"/>
				<input type="checkbox"/>	Stainless Fibre
				<input type="checkbox"/>	Stainless Mesh
<b>Micron rating</b>	<input type="text"/>	µm			
<b>Cleanliness level</b>	<input type="text"/>	(to ISO 4406)			
<b>Information on the application</b>	<input type="text"/>				
<b>Information on the ambient conditions</b>	<input type="text"/>				
<b>Additional information and requirements</b>	<input type="text"/>				



## Return-Line Filters ▪ Type RFB


**Product Description**

STAUFF RFB Return-Line Filters are designed as tank top filters. They are mounted directly on the tank top and if 100% of the system oil is filtered they provide the optimum removal of contaminant from the system. This provides the pump with clean oil thus reducing contaminant generated wear. Because of its low weight and compact design, the STAUFF RFB Filters are ideally suited for mobile hydraulic applications. A high efficiency of contaminant removal is assured by using STAUFF RE Replacement Filter Elements. The high dirt-hold capacity of STAUFF Elements ensures a long service life and as a result reduced maintenance costs.

**Technical Data**
**Construction**

- Tank Top flange mounting

**Materials**

- Filter head: Aluminium
- Filter bowl & cap: Glass Fibre Reinforced Polyamide
- Sealings: NBR (Buna-N®)  
FKM (Viton®)  
EPDM (Ethylene Propylene Diene Monomer Rubber)  
Other sealing materials on request

**Port Connections**

- BSP
- NPT
- SAE O-ring thread

**Operating Pressure**

- Max. 10 bar / 145 PSI

**Temperature Range**

- -10 °C ... +100 °C / +14 °F ... +212 °F

**Filter Elements**

- Specifications see page 88

**Media Compatibility**

- Mineral oils, other fluids on request

**Options and Accessories**
**Valve**

- Bypass valve (integrated in the filter element) Opening pressure 3 bar ± 0,3 bar / 43.5 PSI ± 4.35 PSI  
Other settings available on request


**Clogging Indicators**

- For clogging indicator types please see page 89



Return-Line Filters ▪ Type RFB

D



\* recommended space for element change



## Return-Line Filters ▪ Type RFB

Thread Connection G	Filter Size RFB					
	022		046		052	
BSP	3/4	1	3/4	1	3/4	1
NPT	3/4	1	3/4	1	3/4	1
SAE O-ring Thread	1-5/16-12					

Dimensions (mm/in)	Filter Size RFB		
	022	046	052
h1	34	34	34
	1.34	1.34	1.34
h2	46,5	46,5	46,5
	1.83	1.83	1.83
h3	80	80	80
	3.15	3.15	3.15
h4	205,5	285,5	351,5
	8.09	11.24	13.84
h5	23	23	23
	.91	.91	.91
h6	154	239	305
	6.26	9.41	12.01
d1	32	32	32
	1.26	1.26	1.26
d2	70	70	70
	2.76	2.76	2.76
d3	84,5	84,5	84,5
	3.33	3.33	3.33
b1	72	72	72
	2.84	2.84	2.84
b2	70	70	70
	2.76	2.76	2.76
b3	115,5	115,5	115,5
	4.55	4.55	4.55
b4	138,5	138,5	138,5
	5.45	5.45	5.45
b5	43	43	43
	1.69	1.69	1.69
b6	11	11	11
	.43	.43	.43
b7	58	58	58
	2.28	2.28	2.28

D





## Return-Line Filter Housings / Complete Filters ■ Type RFB

**RFB** - **022** - **G** - **10** - **B** - **G16** - **G42NO** - **D** - **G** - **L10** / **X**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

## ① Type

Return-Line Filter **RFB**

## ② Group

Flow	Size
75 l/min / 22 US GPM	<b>022</b>
165 l/min / 46 US GPM	<b>046</b>
185 l/min / 52 US GPM	<b>052</b>

Note: Exact flow will depend on the selected filter element.  
For technical data please see page 91.

## ③ Filter Material

Material	Max. $\Delta p$ *collapse	Micron ratings available	Code
Without filter element	-	-	<b>O</b>
Inorg. glass fibre	25 bar / 363 PSI	3, 5, 10, 20	<b>G</b>
Stainless fibre	30 bar / 435 PSI		<b>M</b>
Filter paper	10 bar / 145 PSI	10, 20	<b>N</b>
Stainless mesh	30 bar / 435 PSI	10, 25, 50, 100, 200	<b>S</b>

Note: \*Collapse/burst resistance as per ISO 2941.  
Other materials on request.

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
20 $\mu$ m	<b>20</b>
25 $\mu$ m	<b>25</b>
50 $\mu$ m	<b>50</b>
100 $\mu$ m	<b>100</b>
200 $\mu$ m	<b>200</b>

Note: Other micron ratings on request.

## ⑤ Sealing Material

NBR (Buna®)	<b>B</b>
FKM (Viton®)	<b>V</b>
EPDM	<b>E</b>

Note: Other sealing materials on request.

## ⑥ Connection Style

Connection Style		Code
BSP	1	<b>G16</b>
BSP	3/4	<b>G12</b>
NPT	1	<b>N16</b>
NPT	3/4	<b>N12</b>
SAE-O-ring Thread	1-5/16-12	<b>U16</b>

Note: Bold types identify preferred connection style.

## ⑦ Clogging Indicator

Without Clogging Indicator	<b>O</b>
Visual Clogging Indicator	<b>V</b>
Electrical Clogging Switch 42 V, NO	<b>G42NO</b>
Electrical Clogging Switch 42 V, NC	<b>G42NC</b>
Electrical Clogging Switch 110 V ... 230 V, two-way contact (only for Code W)	<b>G230</b>

## ⑧ Option Clogging Indicator G42NO, G42NC and G230

Plug connector	<b>O</b>
M12 x 1,5	<b>M12</b>
AMP plug	<b>A</b>
Deutsch plug	<b>D</b>
Rubber boot	<b>S</b>
90 degree Polyamide cap (only for Code G230)	<b>W</b>

## ⑨ Outlet Style

With 1" BSP thread	<b>G16</b>
With 1" NPT thread	<b>N16</b>

## ⑩ Air Filter Element

Without Air Filter Element	<b>none</b>
Filter paper 10 micron	<b>L10</b>

Note: Other materials and micron ratings on request.

## ⑪ Design Code

Only for information	<b>X</b>
----------------------	----------

## Filter Elements ■ Type RE

**RE** - **022** - **G** - **10** - **B** / **X**

① ② ③ ④ ⑤ ⑥

## ① Type

Filter Element Series **RE**

## ② Group

According to filter housing

## ③ Filter Material

Material	Max. $\Delta p$ *collapse	Micron ratings available	Code
Inorg. glass fibre	25 bar / 363 PSI	3, 5, 10, 20	<b>G</b>
Stainless fibre	30 bar / 435 PSI		<b>M</b>
Filter paper	10 bar / 145 PSI	10, 20	<b>N</b>
Stainless mesh	30 bar / 435 PSI	25, 50, 100, 200	<b>S</b>

Note: \*Collapse/burst resistance as per ISO 2941.  
Other materials on request.

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
20 $\mu$ m	<b>20</b>
25 $\mu$ m	<b>25</b>
50 $\mu$ m	<b>50</b>
100 $\mu$ m	<b>100</b>
200 $\mu$ m	<b>200</b>

Note: Other micron ratings on request.

## ⑤ Sealing Material

NBR (Buna®)	<b>B</b>
FKM (Viton®)	<b>V</b>
EPDM	<b>E</b>

Note: Other sealing material on request.

## ⑥ Design Code

Only for information	<b>X</b>
----------------------	----------

## Air Filter Element

**KIT-RFB-AIR** - **L** - **10** / **X**

① ② ③ ④

## ① Type

Air filter for RFB-022/046/052 **KIT-RFB-AIR**

## ② Filter Material

Filter Paper **L**

Note: Other materials on request.

## ③ Micron Rating

10 $\mu$ m	<b>10</b>
------------	-----------

Note: Other micron ratings on request.

## ④ Design Code

Only for information	<b>X</b>
----------------------	----------



## Return-Line Filters ■ Type RFB

## Electrical Clogging Switch

The switch is used where an electrical signal is needed to indicate when the element needs to be changed. The switch can turn on a light, or shut the machine down, or any further function controlled by an electric signal. The switching pressure is 2,5 bar / 36.25 PSI and this allows the element to be changed before the bypass setting of 3 bar / 43.5 PSI is reached.

Standard type with plug connector and rubber cap. Available with DEUTSCH DT04-2P plug (industrial standard), AMP Junior Timer plug (industrial standard) and five-pin circular connector M12, A-coded, according to IEC 61076-2-101.

## Technical Data

	Limit-Switch G42NO+NC	Limit-Switch G230
Switching Capacity	100 VA	1000 VA
Voltage	10...42 VAC	10...250 VAC
Current		10mA...4A
Switching Accuracy		± 0,5 bar at room temp. and new state
Switching Frequency		200/min
max. Pressure Ramp Rate		≤ 1 bar/ms
Degree of Protection	IP65 (plug type S and W), IP67 (plug type M12, A, D)	
Temperature Range	-30°C ... +100°C	-40°C ... +100°C

## Order Code

**Limit-Switch - G42NO - S - M10 - B2.5**

①

②

③

④

⑤

## ① Type

Limit-Switch

## ② Connector Type

Electrical Clogging Switch 42 V, NO	<b>G42NO</b>
Electrical Clogging Switch 42 V, NC	<b>G42NC</b>
Electrical Clogging Switch 110 V ... 230 V, two-way contact (only for Plug Type W)	<b>G230</b>

## ③ Plug Type

M12 Five-Pin Connector according to IEC 61076-2-101	<b>M12</b>
AMP-Junior-Timer Plug	<b>A</b>
DEUTSCH Plug DT04-2P	<b>D</b>
Rubber boot	<b>S</b>
90 degree Polyamide cap (only for Connector Type G230)	<b>W</b>


## ④ Thread Type

 M10 x 1 **M10**

## ⑤ Pressure Setting

 2,5 bar / 36.3 PSI **B2.5**

## Dimensions Plug Type



Note: The customer / user carries the responsibility for the electrical connection.



## Return-Line Filters - Type RFB

### Visual Clogging Indicator

The gauge visually displays the degree of contamination of the element.  
The colored segments allow quick visual checking.

green	0 ... 2,5 bar / 0 ... 36.25 PSI	Element has service life left
yellow	2,5 ... 3,0 bar / 36.25 ... 43.5 PSI	Element is contaminated and should be changed
red	>3,0 bar / >43.5 PSI	Bypass valve open, unfiltered oil passing to tank


### Order Codes

**SPG-C-040-00004-02-P-M10-402922**




#### ① Type

Visual Clogging Indicator **SPG-C-040-00004-02-P-M10-402922**




### Filter Bowl with Threaded Connection

Under some circumstances such as a tall reservoir or one with oil levels which vary greatly during operation, it is necessary to extend the filter bowl so that the returning oil returns beneath the surface and does not entrain air in the process. The bowl with a female thread allows an extension to be fitted quite simply.



### Air Filter Element

Allows an effective filtration of the incoming air which avoids the infiltration of dirt particles into the hydraulic system. The standard air filter element is a 10 micron cellulose; other materials and micron ratings on request.



### Order Code

**REA-046-L-10-B**




#### ① Type

Air Filter Element **REA-046-L-10-B**

### Filter Bowl with Threaded Connection and Diffuser










Diffusers mounted to the filter bowl minimise foaming and reduce noise of high Return-Line flows. For further details on STAUFF Diffusers please refer to the Catalogue No. 10 - Hydraulic Accessories. Attention: Connection pipe not included in scope of delivery!

Size SRV	for Return-Line Filter Size	Dimensions (mm/in)		Thread G	Hex
		øD	L		
SRV-114-G16	RFB-022/046/052	60	139	G1	46
SRV-114-N16		2.36	5.47	1 NPT	1.81



Return-Line Filters ■ Type RFB Flow Characteristics

The following characteristics are valid for mineral oils with a density of 0,85 kg/dm<sup>3</sup> and the kinematic viscosity of 30 mm<sup>2</sup>/s (30cSt). The characteristics have been determined in accordance to ISO 3968. Multipass filter ratings have been obtained in accordance to ISO 16889. The housing pressure drop is directly proportional to the oil density. Contact STAUFF for details.



### Checklist for the selection of filter housings

Please use the following Checklist as a guideline when preparing an enquiry for the selection of filter housings. Scan or copy the page from the catalogue, print and com-

plete it with as much information as possible, before sending it by email or fax to the closest STAUFF branch office. If possible, please also let us know the quantities required,

and if the enquiry is for a one-time or recurring demand. We look forward to hearing from you, and are always available for consultation, when required.

D

<b>Information on the fluid in use</b>					
<b>Type of fluid</b>	<input type="text"/>	Brand	<input type="text"/>	ISO designation	
<b>Fluid viscosity</b>	<input type="text"/>	<input type="checkbox"/>	mm <sup>2</sup> /sec	<input type="checkbox"/>	cSt
<b>Fluid temperature</b>	<input type="text"/>	°C	<input type="checkbox"/>	°F	<input type="text"/>
			<input type="checkbox"/>	In cold condition	<input type="text"/>
					<input type="checkbox"/>
				In warm condition	
<b>Information on the filter housing</b>					
<b>Position in the hydraulic system</b>	<input type="checkbox"/>	Suction line	<input type="checkbox"/>	Pressure line	<input type="checkbox"/>
				Return line	
<b>Operating pressure</b>	<input type="text"/>	<input type="checkbox"/>	bar	<input type="checkbox"/>	PSI
<b>Nominal flow</b>	<input type="text"/>	<input type="checkbox"/>	l/min	<input type="checkbox"/>	US GPM
<b>Valve</b>	<input type="checkbox"/>	No, not required			
	<input type="checkbox"/>	Yes, the following type:	<input type="checkbox"/>	Bypass valve	<input type="checkbox"/>
			<input type="checkbox"/>	Non-return valve	<input type="checkbox"/>
			<input type="checkbox"/>	Reverse flow valve	<input type="checkbox"/>
			<input type="checkbox"/>	Multi-function valve	
<b>Clogging indicator</b>	<input type="checkbox"/>	No, not required			
	<input type="checkbox"/>	Yes, the following type:	<input type="checkbox"/>	Visual	<input type="checkbox"/>
			<input type="checkbox"/>	Electrical	<input type="checkbox"/>
			<input type="checkbox"/>	Visual-electrical	
<b>Connection type and size</b>	<input type="text"/>				
<b>Sealing material</b>	<input type="checkbox"/>	NBR (Buna®)	<input type="checkbox"/>	FKM (Viton®)	<input type="text"/>
				Other	
<b>Information on the filter element</b>					
<b>Filter media</b>	<input type="checkbox"/>	Inorganic Glass Fibre	<input type="checkbox"/>	Polyester Fibre	<input type="checkbox"/>
			<input type="checkbox"/>	Cellulose Fibre	<input type="checkbox"/>
				Stainless Fibre	<input type="checkbox"/>
				Stainless Mesh	
<b>Micron rating</b>	<input type="text"/>	µm			
<b>Cleanliness level</b>	<input type="text"/>	(to ISO 4406)			
<b>Information on the application</b>	<input type="text"/>				
<b>Information on the ambient conditions</b>	<input type="text"/>				
<b>Additional information and requirements</b>	<input type="text"/>				



## Return-Line Filters ■ Type RFS / RFS-D



D

**Product Description**

STAUFF RFS and RFS-D Carbon Steel Return-Line Filters are designed as tank top or in-line filters. They are mounted directly on the tank top and if 100% of the system oil is filtered, they provide the optimum removal of contaminants from the system. This provides the pump with clean oil thus reducing contaminant generated wear. The filter bowl is designed with a connection, threaded or flanged, for extending the return oil beneath the surface thus preventing the entrainment of air. A high efficiency of contaminant removal is assured by using STAUFF RE Replacement Filter Elements. The high dirt-hold capacity of STAUFF Elements ensures a long service life and as a result reduced maintenance costs.

**Technical Data**
**Construction**

- Tank Top mounting or in-line mounting

**Materials**

- Filter Housing: Carbon Steel
- Sealings: NBR (Buna-N®)  
FKM (Viton®)  
EPDM (Ethylene Propylene Diene Monomer Rubber)  
Other sealing materials on request

**Port Connections**

- BSP
- SAE flange 3000 PSI

**Flow Rating**

- Up to 1135 l/min / 300 US GPM

**Operating Pressure**

- Max. 25 bar / 365 PSI

**Proof Pressure**

- Min. 37,5 bar / 545 PSI

**Temperature Range**

- -10°C ... +100°C / +14°F ... +212°F

**Filter Elements**

- Specifications see page 98

**Media Compatibility**

- Mineral oils, other fluids on request

**Options and Accessories**
**Valve**

- Bypass valve (integrated in the filter element) Opening pressure 3 bar ± 0,3 bar / 43.5 PSI ± 4.35 PSI  
Other settings available on request




**Clogging Indicators**

- For clogging indicator types please see page 99




Return-Line Filters ■ Type RFS

D




RFS-250/300



\* recommended space for element change



RFS-D-090/160



D

\* recommended space for element change







Return-Line Filters ■ Type RFS-D

D


RFS-D-250/300



Top View



Bottom View



\* recommended space for element change



## Return-Line Filters ■ Type RFS / RFS-D

Thread Connection		Filter Size								
		RFS-045	RFS-090	RFS-D-090	RFS-160	RFS-D-160	RFS-250	RFS-D-250	RFS-300	RFS-D-300
Inlet	BSP	1-1/4	2	2	-	-	-	-	-	-
	SAE Flange	-	2	2	3	3	3-1/2	4	4	4
Outlet G	BSP	1-1/4	2	2	3	3	-	-	-	-
	SAE Flange	-	-	-	-	-	3-1/2	3-1/2	4	4

Dimensions (mm/in)	Filter Size								
	RFS-045	RFS-090	RFS-D-090	RFS-160	RFS-D-160	RFS-250	RFS-D-250	RFS-300	RFS-D-300
b1	120	150	150	196	196	255	255	255	255
	4.72	5.91	5.91	7.72	7.72	10.04	10.04	10.04	10.04
b2	95,5	120	120	155,5	155,5	205	205	205	205
	3.76	4.72	4.72	6.12	6.12	8.07	8.07	8.07	8.07
b3	66	85	69	110	100	135	140	145	140
	2.60	3.35	2.72	4.33	3.94	5.32	5.51	5.71	5.51
b4	-	77,8	77,8	106,4	106,4	120,7	130,2	130,2	130,2
	-	3.06	3.06	4.19	4.19	4.75	5.13	5.13	5.13
b5	-	42,9	42,9	61,9	61,9	69,5	77,8	77,8	77,8
	-	1.69	1.69	2.44	2.44	2.74	3.06	3.06	3.06
b6	-	-	254	-	330	-	390	-	410
	-	-	10	-	12.99	-	15.15	-	16.14
b7	-	-	404	-	525	-	640	-	660
	-	-	15.91	-	20.67	-	25.20	-	25.98
b8	-	-	-	-	-	-	120,7	-	130,2
	-	-	-	-	-	-	4.75	-	5.13
b9	-	-	-	-	-	-	69,5	-	77,8
	-	-	-	-	-	-	2.74	-	3.06
d1	100	135	135	180	180	208	208	208	208
	3.94	5.32	5.32	7.09	7.09	8.19	8.19	8.19	8.19
d2	6,5	9	9	13,5	13,5	17,5	17,5	17,5	17,5
	.26	.35	.35	.53	.53	.69	.69	.69	.69
d3	-	M12	M12	M16	M16	M16	M16	M16	M16
	-	1/2-UNC	1/2-UNC	5/8-UNC	5/8-UNC	5/8 UNC	5/8 UNC	5/8 UNC	5/8 UNC
h1	120	138	138	243	243	251	251	332	332
	4.72	5.43	5.43	9.57	9.57	9.88	9.88	13.07	13.07
h2	88	131	131	167	167	198	198	241	241
	3.47	5.16	5.16	6.57	6.57	7.80	7.80	9.49	9.49
h3	43	63	63	84	84	93	93	121	121
	1.69	2.48	2.48	3.31	3.31	3.66	3.66	4.76	4.76
h4	13	13	13	13	13	13	13	13	13
	.51	.51	.51	.51	.51	.51	.51	.51	.51
h5	7	12	12	12	12	24	24	24	24
	.28	.47	.47	.47	.47	.95	.95	.95	.95
h6	130	180	180	320	320	350	350	460	460
	5.11	7.09	7.09	12.60	12.60	13.78	13.78	18.11	18.11
h7	-	-	314	-	450	-	525	-	630
	-	-	12.36	-	17.72	-	20.67	-	24.80

D



## Return-Line Filter Housings / Complete Filters ■ Type RFS / RFS-D

**RFS** - **045** - **G** - **10** - **B** - **G20** - **G42NO** - **D** - **G20** / **X**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

## ① Type

Single Carbon Steel Return-Line Filter	<b>RFS</b>
Double Carbon Steel Return-Line Filter	<b>RFS-D</b>

## ② Group

Flow	Size
170 l/min / 45 US GPM (not for RFS-D)	<b>045</b>
340 l/min / 90 US GPM	<b>090</b>
600 l/min / 160 US GPM	<b>160</b>
945 l/min / 250 US GPM	<b>250</b>
1135 l/min / 300 US GPM	<b>300</b>

Note: Exact flow will depend on the selected filter element.  
For technical data please see pages 101 / 102.

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Without filter element	-	-	<b>O</b>
Inorg. glass fibre	25 bar / 363 PSI	3, 5, 10, 20	<b>G</b>
Stainless fibre	30 bar / 435 PSI		<b>A</b>
Filter paper	10 bar / 145 PSI	10, 20	<b>N</b>
Stainless mesh	30 bar / 435 PSI	25, 50, 100, 200	<b>S</b>

Note: \*Collapse/burst resistance as per ISO 2941.  
Other materials on request.

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
20 $\mu$ m	<b>20</b>
25 $\mu$ m	<b>25</b>
50 $\mu$ m	<b>50</b>
100 $\mu$ m	<b>100</b>
200 $\mu$ m	<b>200</b>

Note: Other micron ratings on request.

## ⑤ Sealing Material

NBR (Buna®)	<b>B</b>
FKM (Viton®)	<b>V</b>
EPDM	<b>E</b>

Note: Other sealing materials on request.

## ⑩ Design Code

Only for information **X**

## ⑥ Connection Style

Connection Style	Thread Style	Group 045	Code	Group 090	Code	Group 160	Code	Group 250	Code	Group 250* / 300	Code
BSP	-	1-1/4	<b>G20</b>	2	<b>G32</b>	-	-	-	-	-	-
SAE Flange 3000 PSI	metric	-	-	2	<b>C332M</b>	3	<b>C348M</b>	3-1/2	<b>C356M</b>	4	<b>C364M</b>
SAE Flange 3000 PSI	UNC	-	-	2	<b>C332U</b>	3	<b>C348U</b>	3-1/2	<b>C356U</b>	4	<b>C364U</b>

\* Note: Only for RFS-D-250.

## ⑦ Clogging Indicator

Without Clogging Indicator	<b>O</b>
Visual Clogging Indicator	<b>V</b>
Electrical Clogging Switch 42 V, NO	<b>G42NO</b>
Electrical Clogging Switch 42 V, NC	<b>G42NC</b>
Electrical Clogging Switch 110 V ... 230 V, two-way contact (only for Code W)	<b>G230</b>

## ⑧ Option Clogging Indicator G42NO, G42NC and G230

Plug connector	<b>O</b>
M12 x 1,5	<b>M12</b>
AMP plug	<b>A</b>
Deutsch plug	<b>D</b>
Rubber boot	<b>S</b>
90 degree Polyamide cap (only for Code G230)	<b>W</b>

## ⑨ Outlet Style

Connection Style	Thread Style	Group 045	Code	Group 090	Code	Group 160	Code	Group 250	Code	Group 300	Code
BSP	-	1-1/4	<b>G20</b>	2	<b>G32</b>	3	<b>G48</b>	-	-	-	-
SAE Flange 3000 PSI	metric	-	-	-	-	-	-	3-1/2	<b>C356M</b>	4	<b>C364M</b>
SAE Flange 3000 PSI	UNC	-	-	-	-	-	-	3-1/2	<b>C356U</b>	4	<b>C364U</b>

## Filter Elements ■ Type RE

**RE** - **045** - **G** - **10** - **B** / **X**

① ② ③ ④ ⑤ ⑥

## ① Type

Filter Element Series	<b>RE</b>
-----------------------	-----------

## ② Group

According to filter housing

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Inorg. glass fibre	25 bar / 363 PSI	3, 5, 10, 20	<b>G</b>
Stainless fibre	30 bar / 435 PSI		<b>A</b>
Filter paper	10 bar / 145 PSI	10, 20	<b>N</b>
Stainless mesh	30 bar / 435 PSI	25, 50, 100, 200	<b>S</b>

Note: \*Collapse/burst resistance as per ISO 2941.  
Other materials on request.

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
20 $\mu$ m	<b>20</b>
25 $\mu$ m	<b>25</b>
50 $\mu$ m	<b>50</b>
100 $\mu$ m	<b>100</b>
200 $\mu$ m	<b>200</b>

Note: Other micron ratings on request.

## ⑤ Sealing Material

NBR (Buna®)	<b>B</b>
FKM (Viton®)	<b>V</b>
EPDM	<b>E</b>

Note: Other sealing materials on request.

## ⑥ Design Code

Only for information **X**



## Return-Line Filters ■ Type RFS / RFS-D

## Electrical Clogging Switch

The switch is used where an electrical signal is needed to indicate when the element needs to be changed. The switch can turn on a light, or shut the machine down, or any further function controlled by an electric signal. The switching pressure is 2,5 bar / 36.25 PSI and this allows the element to be changed before the bypass setting of 3 bar / 43.5 PSI is reached.

Standard type with plug connector and rubber cap. Available with DEUTSCH DT04-2P plug (industrial standard), AMP Junior Timer plug (industrial standard) and five-pin circular connector M12, A-coded, according to IEC 61076-2-101.

## Technical Data

	Limit-Switch G42NO+NC	Limit-Switch G230
Switching Capacity	100 VA	1000 VA
Voltage	10...42 VAC	10...250 VAC
Current		10mA...4A
Switching Accuracy		± 0,5 bar at room temp. and new state
Switching Frequency		200/min
max. Pressure Ramp Rate		≤ 1 bar/ms
Degree of Protection		IP65 (plug type S and W), IP67 (plug type M12, A, D)
Temperature Range	-30°C ... +100°C	-40°C ... +100°C

## Order Code

**Limit-Switch - G42NO - S - M10 - B2.5**

①

②

③

④

⑤

## ① Type

Limit-Switch

## ② Connector Type

Electrical Clogging Switch 42 V, NO	<b>G42NO</b>
Electrical Clogging Switch 42 V, NC	<b>G42NC</b>
Electrical Clogging Switch 110 V ... 230 V, two-way contact (only for Plug Type W)	<b>G230</b>

## ③ Plug Type

M12 Five-Pin Connector according to IEC 61076-2-101	<b>M12</b>
AMP-Junior-Timer Plug	<b>A</b>
DEUTSCH Plug DT04-2P	<b>D</b>
Rubber boot	<b>S</b>
90 degree Polyamide cap (only for Connector Type G230)	<b>W</b>


## ④ Thread Type

 M10 x 1 **M10**

## ⑤ Pressure Setting

 2,5 bar / 36.3 PSI **B2.5**

## Dimensions Plug Type



Note: The customer / user carries the responsibility for the electrical connection.



## Return-Line Filters ▪ Type RFS / RFS-D

### Visual Clogging Indicator

The gauge visually displays the degree of contamination of the element.  
The colored segments allow quick visual checking.

green	0 ... 2,5 bar / 0 ... 36.25 PSI	Element has service life left
yellow	2,5 ... 3,0 bar / 36.25 ... 43.5 PSI	Element is contaminated and should be changed
red	>3,0 bar / >43.5 PSI	Bypass valve open, unfiltered oil passing to tank


### Order Codes

**SPG-C-040-00004-02-P-M10-402922**

①


#### ① Type

Visual Clogging Indicator **SPG-C-040-00004-02-P-M10-402922**



### Leakage Oil Connection


Seal or case drain lines can be connected to the filter through either of the clogging indicator ports providing that the leakage oil can accept a pressure of 3 bar / 43.5 PSI. It ensures that no unfiltered oil can return to the reservoir.



### Filter Bowl with Threaded Connection and Diffuser

Diffusers mounted to the filter bowl minimise foaming and reduce noise of high Return-Line flows. For further details on STAUFF Diffusers please refer to the Catalogue No. 10 - Hydraulic Accessories.  
Attention: Connection pipe not included in scope of delivery!










Size SRV	for Return-Line Filter Size	Dimensions (mm/in)		Thread G	Hex
		øD	L		
SRV-227-G24	RFS-250	84	200	G1-1/2	60
SRV-227-N24		3.31	7.87	1-1/2 NPT	2.36
SRV-454-G32	RFS-250	84	260	G2	70
SRV-454-N32		3.31	10.24	2 NPT	2.76
SRV-950-G24	RFS-250	148	272	G3	100
SRV-950-N24		5.83	10.71	3 NPT	3.94



### Return-Line Filters ■ Type RFS Flow Characteristics

The following characteristics are valid for mineral oils with a density of 0,85 kg/dm<sup>3</sup> and the kinematic viscosity of 30 mm<sup>2</sup>/s (30cSt). The characteristics have been determined in accordance to ISO 3968. Multipass filter ratings have been obtained in accordance to ISO 16889. The housing pressure drop is directly proportional to the oil density. Contact STAUFF for details.







D



### Return-Line Filters - Type RFS Flow Characteristics

The following characteristics are valid for mineral oils with a density of 0,85 kg/dm<sup>3</sup> and the kinematic viscosity of 30 mm<sup>2</sup>/s (30cSt). The characteristics have been determined in accordance to ISO 3968. Multipass filter ratings have been obtained in accordance to ISO 16889. The housing pressure drop is directly proportional to the oil density. Contact STAUFF for details.

D



## Return-Line Filters ■ Type RTF-10/15/25



D

**Product Description**

STAUFF RTF-10/15/25 Return-Line Filters are designed as tank top filters with a maximum operating pressure of 3,4 bar / 49 PSI.

**Technical Data**
**Construction**

- Tank Top flange mounting

**Materials**

- Filter head: Aluminium
- Filter bowl: Polyamide
- Sealings: NBR (Buna-N®)  
FKM (Viton®)  
Other sealing materials on request

**Port Connections**

- BSP
- NPT
- SAE O-ring thread

**Flow Rating**

- Up to 95 l/min / 25 US GPM

**Operating Pressure**

- Max. 3,4 bar / 49 PSI

**Burst Pressure**

- Min. 10 bar / 145 PSI

**Temperature Range**

- -25 °C ... +95 °C / -13 °F ... +203 °F

**Filter Elements**

- Specifications see page 106

**Media Compatibility**

- Mineral oils, other fluids on request

**Options and Accessories**
**Valve**

- Bypass valve: Opening pressure 1,7 bar / 25 PSI  
(integrated in the filter element)  
Other settings available on request

**Clogging Indicators**


- For clogging indicator types please see page 125





Return-Line Filters ▪ Type RTF-10/15/25

D



\* recommended space for element change



## Return-Line Filters ■ Type RTF-10/15/25

Thread Connection G	Filter Size RTF		
	10	15	25
BSP	1/2	1	1
NPT	1/2	1	1
SAE O-ring	-	1-5/16-12	1-5/16-12

Dimensions (mm/in)	Filter Size RTF		
	10	15	25
h1	26	34	34
	1.02	1.34	1.34
h2	21	29	29
	.83	1.14	1.14
h3	89	103	149
	3.50	4.05	5.87
h4	136	166	212
	5.35	6.53	8.35
h5	8	10	10
	.32	.39	.39
h6	110	130	175
	4.33	5.12	6.89
b1	50	67	67
	1.97	2.64	2.64
b2	90	115	115
	3.54	4.52	4.52
d1	66	86	86
	2.60	3.39	3.39
d2	24	28	28
	.94	1.10	1.10
d3	7	9	9
	.28	.35	.35
Weight (kg/lbs)	0,45	0,9	1
	1	2	2.2

D



## Return-Line Filter Housings / Complete Filters ■ Type RTF-10/15/25

**RTF** - **25** - **D** - **10** - **B** - **G16** - **V** / **X**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

## ① Type

Return-Line Filter **RTF**

## ② Group

Flow	Size
38 l/min / 10 US GPM	<b>10</b>
57 l/min / 15 US GPM	<b>15</b>
95 l/min / 25 US GPM	<b>25</b>

Note: Exact flow will depend on the selected filter element.  
For technical data please see pages 123 / 124.

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Without filter element	-	-	<b>0</b>
Inorg. glass fibre	3 bar / 43.5 PSI	10, 25	<b>G</b>
Filter paper	3 bar / 43.5 PSI	10, 25	<b>D</b>

\*Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

## ④ Micron Rating

10 $\mu$ m	<b>10</b>
25 $\mu$ m	<b>25</b>

Note: Other micron ratings on request

## ⑤ Sealing Material

NBR (Buna®) **B**  
FKM (Viton®) **V**  
Note: Other sealing materials on request

## ⑥ Connection Style

Connection Style	Group 10	Code	Group 25 and 15	Code
BSP	1/2	<b>G08</b>	1	<b>G16</b>
NPT	1/2	<b>N08</b>	1	<b>N16</b>
SAE O-ring Thread	-	-	1-5/16-12	<b>U16</b>

## ⑦ Clogging Indicator

Without clogging indicator **0**  
Visual clogging indicator **V**  
Electrical clogging indicator **E**  
Note: See page 125 for more details on indicator ports and types.

## ⑧ Design Code

Only for information **X**

## Filter Elements ■ Type RTE

**RTE** - **25** - **D** - **10** - **B** / **X**

① ② ③ ④ ⑤ ⑥

## ① Type

Filter Element Series **RTE**

## ② Group

According to filter housing

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Inorg. glass fibre	3 bar / 43.5 PSI	10, 25	<b>G</b>
Filter paper	3 bar / 43.5 PSI	10, 25	<b>D</b>

\* Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

## ④ Micron Rating

10 $\mu$ m	<b>10</b>
25 $\mu$ m	<b>25</b>

Note: Other micron ratings on request

## ⑤ Sealing Material

NBR (Buna®) **B**  
FKM (Viton®) **V**  
Note: Other sealing materials on request

## ⑥ Design Code

Only for information **X**



## Return-Line Filters ■ Type RTF-20



D

**Product Description**

STAUFF RTF-20 Return-Line Filters are designed as tank top filters with a maximum operating pressure of 10 bar / 145 PSI and flow rates up to 115 l/min / 30 US GPM. The filter bowl is designed to return the oil beneath the surface thus preventing entrainment of air. RTF-20 series compact design and integral breather make them ideal for mobile hydraulic applications.

**Technical Data**
**Construction**

- Tank Top flange mounting

**Materials**

- Filter head: Aluminium
- Filter bowl & cap: Polyamide
- Sealings: NBR (Buna-N®)  
FKM (Viton®)  
Other sealing materials on request

**Port Connections**

- BSP
- NPT
- SAE O-ring thread

**Flow Rating**

- Up to 115 l/min / 30 US GPM

**Operating Pressure**

- Max. 10 bar / 145 PSI

**Burst Pressure**

- Min. 30 bar / 435 PSI

**Temperature Range**

- -25 °C ...+95 °C / -13 °F ... +203 °F

**Integrated Breather**

- Filter paper 10 µm
- Filter paper 40 µm

**Filter Elements**

- Specifications see page 110

**Media Compatibility**

- Mineral oils, other fluids on request

**Options and Accessories**
**Valve**

- Bypass valve: Opening pressure 1,7 bar / 25 PSI  
(integrated in the filter element) Other settings available on request


**Clogging Indicators**

- For clogging indicator types please see page 125



Return-Line Filters ■ Type RTF-20

D



\* recommended space for element change



## Return-Line Filters ■ Type RTF-20

Thread Connection G1	Filter Size RTF 020	
BSP	1/2	3/4
NPT	1/2	3/4
SAE Thread	3/4-16	1-1/16


Dimensions (mm/in)	Filter Size RTF 020	
b1	50	
	1.97	
b2	70	
	2.76	
b3	82	
	3.23	
b4	88	
	3.46	
b5	11	
	.43	
d1	28	
	1.10	
d2*	Min. 60 / Max. 63	
	Min. 2.36 / Max. 2.48	
d3	77	
	3.03	
d4	75	
	2.95	
d5	48	
	1.89	
h1	24	
	.94	
h2	37,5	
	1.48	
h3	178	
	7.01	
h4	202	
	7.95	
h5	16	
	.63	
h6	2	
	.07	
h7	210	
	8.27	
G2	G1/8 or 1/8 NPT	

\* recommended diameter for mounting hole

D



Return-Line Filter Housings / Complete Filters ▪ Type RTF-20



① Type

Return-Line Filter **RTF**

② Group

**Flow** **Size**  
115 l/min / 30 US GPM **20**  
Note: Exact flow will depend on the selected filter element.  
For technical data please see pages 123 / 124..

③ Filter Material

Material	Max. Δp*collapse	Micron ratings available	Code
Without filter element	-	-	<b>0</b>
Inorg. glass fibre	25 bar / 363 PSI	10, 20	<b>G</b>
Filter paper	10 bar / 145 PSI	10	<b>D</b>

\*Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

④ Micron Rating

10 µm **10**  
20 µm **20**  
Note: Other micron ratings on request

⑤ Sealing Material

NBR (Buna®) **B**  
FKM (Viton®) **V**  
Note: Other sealing materials on request

⑥ Connection Style

Connection Style	Thread	Code
BSP	1/2	<b>G08</b>
BSP	3/4	<b>G12</b>
NPT	1/2	<b>N08</b>
NPT	3/4	<b>N12</b>
SAE O-ring Thread	3/4-16	<b>U08</b>
SAE O-ring Thread	1-1/16-12	<b>U12</b>

⑦ Clogging Indicator

No clogging indicator **0**  
Visual clogging indicator **V**  
Electrical clogging indicator **E**  
Note: See page 125 for more details on indicator ports and types.

⑧ Breather

10 µm Filter Paper **L10**  
40 µm Filter Paper **L40**


⑨ Dipstick

Without dipstick (standard) **none**  
With dipstick **D**

⑩ Design Code

Only for information **X**

Filter Elements ▪ Type RTE



① Type

Filter Element Series **RTE**

② Group

According to filter housing

③ Filter Material

Material	Max. Δp*collapse	Micron ratings available	Code
Inorg. glass fibre	25 bar / 363 PSI	10, 20	<b>G</b>
Filter paper	10 bar / 145 PSI	10	<b>D</b>

\*Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

④ Micron Rating

10 µm **10**  
20 µm **20**  
Note: Other micron ratings on request

⑤ Sealing Material

NBR (Buna®) **B**  
FKM (Viton®) **V**  
Note: Other sealing materials on request

⑥ Design Code

Only for information **X**

Air Filter Elements ▪ Type RTEA



① Type

Air Filter Element Series **RTEA**

② Group

Air filter for RTF-20

③ Filter Material

Filter Paper **L**  
Note: Other materials on request

④ Micron Rating

10 µm **10**  
Note: Other micron ratings on request

⑤ Sealing Material

NBR (Buna®) **B**  
Note: Other sealing materials on request

⑥ Design Code

Only for information **X**



## Return-Line Filters ■ Type RTF-40



D

**Product Description**

STAUFF RTF-40 Return-Line Filters are designed as tank top filters with a maximum operating pressure of 6,9 bar / 100 PSI. The filter bowl is designed to return the oil beneath the surface thus preventing entrainment of air.

**Technical Data**
**Construction**

- Tank Top flange mounting

**Materials**

- Filter head: Aluminium
- Filter bowl: Bowl length 1: Polyamide  
Bowl length 2: Steel
- Sealings: NBR (Buna-N®)  
Other sealing materials on request

**Port Connections**

- BSP
- NPT
- SAE O-ring thread
- SAE flange

**Flow Rating**

- Up to 378 l/min / 100 US GPM

**Operating Pressure**

- Max. 6,9 bar / 100 PSI

**Temperature Range**

- -25 °C ... +95 °C / -13 °F ... +203 °F

**Filter Elements**

- RTE-47 with integrated bypass valve, single stack length
- RTE-48 bypass valve integrated in the filter head, equivalent to the HF-4 elements, single and double stack lengths
- RTE-49 bypass valve integrated in the filter head, single and double stack lengths
- Specifications see page 114

**Media Compatibility**

- Mineral oils, other fluids on request

**Options and Accessories**
**Valve**

- Bypass valve: Opening pressures 1 bar / 14.5 PSI ±10 % or  
1,7 bar / 25 PSI ±10 %  
RTF-47: Bypass integrated in the filter element  
RTF-48/49: Bypass integrated in the filter head

**Clogging Indicators**


- For clogging indicator types please see page 125





Return-Line Filters ■ Type RTF-40


D



Filter Elements ■ Types RTE-47 / RTE-48 / RTE-49


RTE-47

- with integrated bypass valve
- single stack length



RTE-48


- bypass valve integrated in the filter head
- equivalent to the HF-4 elements
- single and double stack lengths



Seal: NBR (Buna®)

RTE-49


- bypass valve integrated in the filter head
- single and double stack lengths



Seal: NBR (Buna®)



## Return-Line Filters ■ Type RTF-40


**RTF-40 Series Weld Ring WR-40**

The WR-40 weld ring is welded directly to the hydraulic reservoir, eliminating the need for drilling and tapping mounting holes in the reservoir.

Material: Carbon Steel

Thread Connection Combinations	Filter Size RTF			
	4...S1		4...S2	
	Inlet A	Inlet B	Inlet A	Inlet B
BSP	1-1/4 and 1-1/2 SAE Flange	None	1-1/4 and 1-1/2 SAE Flange	None
BSP	1-1/4 and 1-1/2 SAE Flange	1-1/4	1-1/4 and 1-1/2 SAE Flange	1-1/4
NPT	1-1/4 and 1-1/2 SAE Flange	None	1-1/4 and 1-1/2 SAE Flange	None
NPT	1-1/4 and 1-1/2 SAE Flange	1-1/4	1-1/4 and 1-1/2 SAE Flange	1-1/4
NPT	1-1/2	None	1-1/2	None
NPT	1-1/2	1-1/4	1-1/2	1-1/4
NPT	1-1/2	1-1/2	1-1/2	1-1/2
SAE	1-5/8-12	None	1-5/8-12	None
SAE	1-5/8-12	1-5/8-12	1-5/8-12	1-5/8-12
SAE	1-5/8-12	1-7/8-12	1-5/8-12	1-7/8-12
SAE	1-5/8-12	2-1/2-12	1-5/8-12	2-1/2-12
SAE	1-7/8-12	1-7/8-12	1-7/8-12	1-7/8-12
Combination SAE & NPT	1-5/8-12	2	1-5/8-12	2

Dimensions (mm/in)	Filter Size RTF	
	4...S1	4...S2
h1	50 1.97	50 1.97
h2	112 4.41	112 4.41
h3	263 10.35	475 18.70
h4	385 15.16	587 23.11
h5	21 .83	38 1.50
h6	11 .43	11 .43
b1	170 6.70	170 6.70
b2	152 5.98	152 5.98
b3	69.9 2.75	69.9 2.75
b4	35.6 1.40	35.6 1.40
b5	112 4.41	112 4.41
d1	122 4.80	126 4.96
d2	M12 or 1/2-13 UN	M12 or 1/2-13 UN
d3	38,1 1.50	38,1 1.50
d4	11 .43	11 .43
G	G1-1/2 or 1-1/2 NPT	G1-1/2 or 1-1/2 NPT

Dimensions in mm / in



## Return-Line Filter Housings / Complete Filters ■ Type RTF-40

**RTF** - **48** - **D** - **10** - **B** - **G20+C324M/G20** - **B1** - **S2** - **V** / **X**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

## ① Type

Return-Line Filter **RTF**

## ② Group

Flow	Size
190 l/min / 50 US GPM	<b>47</b>
190 l/min / 50 US GPM	<b>48</b>
190 l/min / 50 US GPM	<b>49</b>

Note: Exact flow will depend on the selected filter element.  
For technical data please see pages 123 / 124.  
For element length 2 (only RTF-48 / RTF-49)  
please double relating flow values.

## ③ Filter Material

Material	Max. $\Delta p$ *collapse	Micron ratings available	Code
Without filter element	-	-	<b>0</b>
Inorg. glass fibre	10 bar / 145 PSI	3, 5, 10, 25	<b>G</b>
Filter paper	10 bar / 145 PSI	10, 25	<b>D</b>

\*Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
25 $\mu$ m	<b>25</b>

Note: Other micron ratings on request

## ⑤ Sealing Material

NBR (Buna®) **B**  
Note: Other sealing materials on request

## ⑥ Connection Style

Connection Style	Group		Code
	Port A	Port B	
BSP	1-1/4 and 1-1/2 SAE Flange	None	<b>G20+C324M/0</b>
BSP	1-1/4 and 1-1/2 SAE Flange	1-1/4	<b>G20+C324M/G20</b>
NPT	1-1/4 and 1-1/2 SAE Flange	None	<b>N20+C324M/0</b>
NPT	1-1/4 and 1-1/2 SAE Flange	1-1/4	<b>N20+C324M/N20</b>
NPT	1-1/2	None	<b>N24/0</b>
NPT	1-1/2	1-1/4	<b>N24/N20</b>
NPT	1-1/2	1-1/2	<b>N24/N24</b>
SAE	1-5/8-12	None	<b>U20/0</b>
SAE	1-5/8-12	1-5/8-12	<b>U20/U20</b>
SAE	1-5/8-12	1-7/8-12	<b>U20/U24</b>
SAE	1-5/8-12	2-1/2-12	<b>U20/U40</b>
SAE	1-7/8-12	1-7/8-12	<b>U24/U24</b>
Combination NPT & SAE	1-5/8-12	2	<b>U20/N32</b>

## ⑦ Valve

No bypass **0**  
1 bar / 15 PSI **B1.0**  
1,7 bar / 24.6 PSI **B1.7**

## ⑧ Length

Bowl Length 1 (1 element) **S1**  
Bowl Length 2 (2 elements) **S2**  
Note: RTF-47 size available in S1 bowl length only.

## ⑨ Clogging Indicator

No clogging indicator **0**  
Visual clogging indicator **V**  
Electrical clogging indicator **E**  
Note: See page 125 for more details on indicator ports and options.

## ⑩ Design Code

Only for information **X**

## Filter Elements ■ Type RTE

**RTE** - **48** - **D** - **10** - **B** / **X**

① ② ③ ④ ⑤ ⑥

## ① Type

Filter Element Series **RTE**

## ② Group

According to filter housing

## ③ Filter Material

Material	Max. $\Delta p$ *collapse	Micron ratings available	Code
Inorg. glass fibre	10 bar / 145 PSI	3, 5, 10, 25	<b>G</b>
Filter paper	10 bar / 145 PSI	10, 25	<b>D</b>

\*Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
25 $\mu$ m	<b>25</b>

Note: Other micron ratings on request

## ⑤ Sealing Material

NBR (Buna®) **B**  
Note: Other sealing materials on request

## ⑥ Design Code

Only for information **X**



## Return-Line Filters ▪ Type RTF-50



D

**Product Description**

STAUFF RTF-50 Return-Line Filters are designed for tank top applications with a maximum pressure of 6,9 bar / 100 PSI. The filter bowl is designed to return the oil beneath the surface thus preventing entrainment of air. The RTF-58 elements interchange with the popular "K" series and RTF-59 elements interchange with the "RE-409" series elements.

**Technical Data**
**Construction**

- Tank Top flange mounting

**Materials**

- Filter head: Aluminium
- Filter bowl: Bowl length 1: Polyamide  
Bowl length 2: Steel
- Sealings: NBR (Buna-N®)  
Other sealing materials on request

**Port Connections**

- BSP
- NPT
- SAE O-ring thread

**Flow Rating**

- Up to 379 l/min / 100 US GPM

**Operating Pressure**

- Max. 6,9 bar / 100 PSI

**Temperature Range**

- -25 °C ... +95 °C / -13 °F ... +203 °F

**Filter Elements**

- Specifications see page 118

**Media Compatibility**

- Mineral oils, other fluids on request

**Options and Accessories**
**Valve**

- Bypass valve: Opening pressures 1 bar / 14.5 PSI  $\pm$ 10 % or 1,7 bar / 25 PSI  $\pm$ 10 %  
Other settings available on request


**Clogging Indicators**

- For clogging indicator types please see page 125




Return-Line Filters ■ Type RTF-50

D



Return-Line Filters ■ Type RTF Accessories



RTF-50 Series Weld Ring WR-40

The WR-40 weld ring is welded directly to the hydraulic reservoir, eliminating the need for drilling and tapping mounting holes in the reservoir.

Material: Carbon Steel

Dimensions in mm / in



## Return-Line Filters ■ Type RTF-50

Thread Connection Combinations	Filter Size RTF			
	5...S1		5...S2	
	Inlet A	Inlet B	Inlet A	Inlet B
NPT (N)	1-1/4	None	1-1/4	None
NPT (NM)	1-1/4	1-1/2	1-1/4	1-1/2
NPT (M)	None	1-1/2	None	1-1/2
Combination SAE & NPT (SM)	1-5/8-12	1-1/2	1-5/8-12	1-1/2
SAE (S)	1-5/8-12	None	1-5/8-12	None
SAE (T)	None	1-7/8-12	None	1-7/8-12
SAE (ST)	1-5/8-12	1-7/8-12	1-5/8-12	1-7/8-12
Combination NPT & SAE (NT)	1-1/4	1-7/8-12	1-1/4	1-7/8-12

Dimensions (mm/in)	Filter Size RTF	
	5...S1	5...S2
h1	49,3	42,3
	1.94	1.67
h2	95,5	88,5
	3.78	3.48
h3	241,3	485,9
	9.50	19.13
h4	336,8	574,9
	13.26	22.61
h5	29,5	38,1
	1.16	1.50
b1	177,8	177,8
	7.00	7.00
d1	124,8	126
	4.91	4.96
d2	158,7	158,7
	6.25	6.25
d3	11,2	11,2
	.44	.44
G	1-1/2 NPT	1-1/2 NPT

D



## Return-Line Filter Housings / Complete Filters ■ Type RTF-50

**RTF** - **58** - **D** - **10** - **B** - **N20/0** - **B1.7** - **S2** - **V** / **X**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

## ① Type

Return-Line Filter **RTF**

## ② Group

Flow	Size
Group size 58	<b>58</b>
Group size 59	<b>59</b>

Note: Exact flow will depend on the selected filter element.  
For technical data please see pages 123 / 124.

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Without filter element	-	-	<b>0</b>
Inorg. glass fibre	10 bar / 145 PSI	3, 5, 10, 25	<b>G</b>
Filter paper	5 bar / 72.5 PSI	10, 25	<b>D</b>

\*Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

## ④ Micron Rating

3 $\mu\text{m}$	<b>03</b>
5 $\mu\text{m}$	<b>05</b>
10 $\mu\text{m}$	<b>10</b>
25 $\mu\text{m}$	<b>25</b>

Note: Other micron ratings on request

## ⑤ Sealing Material

NBR (Buna®) **B**  
Note: Other sealing materials on request

## ⑥ Connection Style

Connection Style	Group		Code
	Port A	Port B	
NPT	1-1/4	None	<b>N20/0</b>
NPT	1-1/4	1-1/2	<b>N20/N24</b>
NPT	None	1-1/2	<b>0/N24</b>
Combination SAE & NPT	1-5/8-12	1-1/2	<b>U20/N24</b>
SAE	1-5/8-12	None	<b>U20/0</b>
SAE	None	1-7/8-12	<b>0/U24</b>
SAE	1-5/8-12	1-7/8-12	<b>U20/U24</b>
Combination NPT & SAE	1-1/4	1-7/8-12	<b>N20/U24</b>

## ⑦ Valve

No bypass	<b>0</b>
1 bar / 15 PSI	<b>B1.0</b>
1,7 bar / 24.6 PSI	<b>B1.7</b>

## ⑧ Length

Bowl Length 1 (1 element)	<b>S1</b>
Bowl Length 2 (2 elements)	<b>S2</b>

## ⑨ Clogging Indicator

No clogging indicator	<b>0</b>
Visual clogging indicator	<b>V</b>
Electrical clogging indicator	<b>E</b>

Note: See page 125 for more details on indicator ports and types.

## ⑩ Design Code

Only for information **X**

## Filter Elements ■ Type RTE

**RTE** - **58** - **D** - **10** - **B** - **X**

① ② ③ ④ ⑤ ⑥

## ① Type

Filter Element Series **RTE**

## ② Group

According to filter housing

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Inorg. glass fibre	10 bar / 145 PSI	3, 5, 10, 25	<b>G</b>
Filter paper	5 bar / 72.5 PSI	10, 25	<b>D</b>

\*Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

## ④ Micron Rating

3 $\mu\text{m}$	<b>03</b>
5 $\mu\text{m}$	<b>05</b>
10 $\mu\text{m}$	<b>10</b>
25 $\mu\text{m}$	<b>25</b>

Note: Other micron ratings on request

## ⑤ Sealing Material

NBR (Buna®) **B**  
Note: Other sealing materials on request

## ⑥ Design Code

Only for information **X**



## Return-Line Filters ■ Type RTF-N



D

**Product Description**

STAUFF RTF-N Return-Line Insert Filters allow for a choice of installation configurations which permits custom reservoir design with an in tank filtering system. The filters are installed semi-immersed or totally immersed into a reservoir. The filtration flow is from inside to the outside of the element which ensures that all the contaminant is collected inside the element itself avoiding contact with the reservoir fluid during element change. The combination of magnetic pre-filtration and high filtration efficiency results in a cost effective and versatile filtration system.

**Technical Data**
**Construction**

- Insert filter

**Materials**

- Flange plate: Aluminium
- Magnet rod: Steel
- Bypass: Steel
- Diffuser: Steel
- Sealings: NBR (Buna-N®)  
FKM (Viton®)  
Other sealing materials on request

**Flow Rating**

- Up to 500 l/min / 132 US GPM

**Operating Pressure**

- Max. 10 bar / 145 PSI

**Temperature Range**

- -29 °C ...+107 °C / -20 °F ... +225 °F

**Filter Elements**

- Specifications see page 122

**Media Compatibility**

- Mineral oils, other fluids on request

**Options and Accessories**
**Valve**





- Bypass valve: Opening pressure 1,5 bar / 22 PSI  
(integrated in the filter element) Other settings available on request





Return-Line Filters ■ Type RTF-N

D



## Return-Line Filters ▪ Type RTF-N

Dimensions (mm/in)	Filter Size RTF-N	
	390	500
h1	445	635
	17.52	25.00
h2	290	478
	11.42	18.82
h3	421	609
	16.57	23.98
h4	5	5
	.20	.20
h5	18	18
	.71	.71
h6	2,5	2,5
	.10	.10
h7	100	100
	3.94	3.94
h8	110	110
	4.33	4.33
d1	185	185
	7.28	7.28
d2	150	150
	5.91	5.91
d3	25	25
	.98	.98
d4	126	126
	4.95	4.95
d5	165	165
	6.50	6.50
d6	151	151
	5.94	5.94
d7	149	149
	5.87	5.87
d8	139	139
	5.47	5.47
d9	178	178
	7.01	7.01

D



## Return-Line Filter Housings / Complete Filters ■ Type RTF-N

RTF-N - 500 - E - 10 - B - B1.5 - D / X

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

## ① Type

Return-Line Insert Filter **RTF-N**

## ② Group

Flow	Size
390 l/min / 103 US GPM	<b>390</b>
500 l/min / 132 US GPM	<b>500</b>

Note: Exact flow will depend on the selected filter element.  
For technical data please see pages 13 / 124.

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Without filter element	-	-	<b>0</b>
Inorg. glass fibre	10 bar / 145 PSI	3, 5, 10, 20	<b>E</b>
Filter paper	10 bar / 145 PSI	10	<b>L</b>

\*Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
20 $\mu$ m	<b>20</b>

Note: Other micron ratings on request

## ⑤ Sealing Material

NBR (Buna®) **B**  
FKM (Viton®) **V**

Note: Other sealing materials on request

## ⑥ Bypass Setting

1,5 bar / 22 PSI **B1.5**

## ⑦ Options

Without diffusor **0**  
With diffusor **D**

## ⑧ Design Code

Only for information **X**

## Filter Elements ■ Type RA

RA - 500 - E - 10 - B / X

① ② ③ ④ ⑤ ⑥

## ① Type

Element for Insert Filter **RA**

## ② Group

According to filter housing

## ③ Filter Material

Material	Max. $\Delta p^*$ collapse	Micron ratings available	Code
Inorg. glass fibre	10 bar / 145 PSI	3, 5, 10, 20	<b>E</b>
Filter paper	10 bar / 145 PSI	10	<b>L</b>

\*Note: Collapse/burst resistance as per ISO 2941  
Other materials on request

## ④ Micron Rating

3 $\mu$ m	<b>03</b>
5 $\mu$ m	<b>05</b>
10 $\mu$ m	<b>10</b>
20 $\mu$ m	<b>20</b>

Note: Other micron ratings on request

## ⑤ Sealing Material

NBR (Buna®) **B**  
FKM (Viton®) **V**

Note: Other sealing materials on request













## ⑥ Design Code

Only for information **X**



Return-Line Filters • Type RTF Flow Characteristics








The following characteristics are valid for mineral oils with a density of 0,85 kg/dm<sup>3</sup> and the kinematic viscosity of 30 mm<sup>2</sup>/s (30cSt). The characteristics have been determined in accordance to ISO 3968. Multipass filter ratings have been obtained in accordance to ISO 16889. The housing pressure drop is directly proportional to the oil density. Contact STAUFF for details.








## Return-Line Filters - Type RTF Flow Characteristics

The following characteristics are valid for mineral oils with a density of 0,85 kg/dm<sup>3</sup> and the kinematic viscosity of 30 mm<sup>2</sup>/s (30cSt). The characteristics have been determined in accordance to ISO 3968. Multipass filter ratings have been obtained in accordance to ISO 16889. The housing pressure drop is directly proportional to the oil density. Contact STAUFF for details.

D





Note: Element pressure drop curves are for "S1" single elements. For "S2" double elements use 50% of the "S1" Value.



## RTF Filter Indicators

## Visual Indicators



SPG-C-...-B02-..



SPG-C-...-N02-...

Visual Pressure Clogging Indicators						Order Code	
Thread Connection G	Unit of scale	Range of scale	Coloured Segments				
			Green	Yellow	Red		
BSP	1/8	bar	0 ... 2,5	0 ... 1,2	1,2 ... 1,5	1,5 ... 2,5	SPG-C-040-00002.5-02-P-B02-402923
	1/8	bar	0 ... 4	0 ... 2,5	2,5 ... 3	3 ... 4	SPG-C-040-00004-02-P-B02-402922
	1/8	bar	0 ... 12	without coloured segments			SPG-C-040-00012-02-P-B02
NPT	1/8	PSI	0 ... 100	0 ... 13	13 ... 15	15 ... 100	SPG-C-040-00100-03-P-N02-402927
	1/8	PSI	0 ... 100	0 ... 21	21 ... 25	25 ... 100	SPG-C-040-00100-03-P-N02-402928

## Electrical Clogging Switch

## Order Code

**Limit-Switch - G42NO - S - B02 - B1.3**

①

②

③

④

⑤

## ① Type

**Limit-Switch**

## ② Connector Type

Electrical Clogging Switch 42 V, NO	<b>G42NO</b>
Electrical Clogging Switch 42 V, NC	<b>G42NC</b>
Electrical Clogging Switch 110 V ... 230 V, two-way contact (only for Plug Type W)	<b>G230</b>

## ③ Plug Type

M12 Five-Pin Connector according to IEC 61076-2-101	<b>M12</b>
AMP-Junior-Timer Plug	<b>A</b>
DEUTSCH Plug DT04-2P	<b>D</b>
Rubber boot	<b>S</b>
90 degree Polyamide cap (only for Connector Type G230)	<b>W</b>


## ④ Thread Type

1/8 BSP	<b>B02</b>
1/8 NPT	<b>N02</b>

## ⑤ Pressure Setting

1,3 bar / 18.8 PSI	<b>B1.3</b>
--------------------	-------------

Note: Technical Data for Limit-Switch types please see Page 73.



Note: The customer / user carries the responsibility for the electrical connection.

Dimensional drawings: All dimensions in mm/in.





## LubeTeam Hydraulic S.r.l.

*Administration and Headquarter:*

Via Tufara Scautieri, 6

83018 - San Martino Valle Caudina (AV)

*Office and Warehouse:*

S.S. 7 Appia, Km. 237,00

82011 - Airola BN

ITALY

Tel. +39 0823 950 994

Fax +39 0823 412 546

[www.lubeteam.it](http://www.lubeteam.it) [info@lubeteam.it](mailto:info@lubeteam.it)

Italian VAT / C.F. e P.IVA: 01251720627

Follow us



This document is the property of LubeTeam Hydraulic S.r.l. All data reported here are for the exclusive use of the Receiver. Reproduction is not authorized without writing permission, in all or in part of the content of this document, in accordance to Law 633 art. 171, dated April 22, 1941.

Il presente documento è di proprietà della LubeTeam Hydraulic S.r.l. I dati riportati sono per esclusivo del destinatario. La riproduzione, di tutto o in parte, non è autorizzata senza permesso scritto secondo l'art. 171 della L. 633 del 22 Aprile 1941.