



CEJN  
Conessioni gas  
Attacchi rapidi per gas



 HYDRAULIC  
COMPONENTS  
& FLUID CONTAMINATION  
CONTROL



All trademarks belong to their respective owners; third party trademarks, product names, trade names, corporate names and company names mentioned may be trademarks of their respective owners or registered trademarks of other companies and are used for instructional purposes and for the benefit of the owner, without any end of Copyright infringement in force.

Tutti i marchi riportati appartengono ai legittimi proprietari; marchi di terzi, nomi di prodotti, nomi commerciali, nomi corporativi e società citati possono essere di proprietà dei rispettivi titolari o registrati da altre società e sono stati utilizzati a puro scopo esplicativo e a beneficio del possessore, senza alcun fine di violazione dei diritti di Copyright vigenti.



# Gas Products

*Dependable products for gas applications*

CEJN's gas product line meets the extra stringent safety demands of gas applications. The products have an automatic safety-locking feature and double seal functions for extra safety protection, plus colour coding on both the couplings and nipples. Presented here are CEJN's couplings and nipples for gas applications.

## Series 171 (CEJN Original)

### Acetylene

- Automatic safety locking feature
- Double seal function for extra safety
- Cross connection between series is impossible

Flow capacity of 720 l/min ( CFM). Max working pressure 10 bar (145 PSI). Made of yellow pickled bras/aluminium with EPDM seals. The couplings and nipples can be equipped with dust caps.



## Series 172 (CEJN Original)

### LP-Gas

- Automatic safety locking feature
- Double seal function for extra safety
- Cross connection between series is impossible

Flow capacity of 720 l/min ( CFM). Max working pressure 10 bar (145 PSI). Made of yellow pickled bras/aluminium with NBR seals. The couplings and nipples can be equipped with dust caps.



## Series 181 (CEJN Original)

### Oxygen

- Automatic safety locking feature
- Double seal function for extra safety
- Cross connection between series is impossible

Flow capacity of 720 l/min ( CFM). Max working pressure 10 bar (145 PSI). Made of yellow pickled bras/ aluminium with EPDM seals. The couplings and nipples can be equipped with dust caps.







## LubeTeam Hydraulic S.r.l.

*Administration and Headquarter:*

Via Tufara Scautieri, 6

83018 - San Martino Valle Caudina (AV)

*Office and Warehouse:*

S.S. 7 Appia, Km. 237,00

82011 - Airola BN

ITALY

Tel. +39 0823 950 994

Fax +39 0823 412 546

[www.lubeteam.it](http://www.lubeteam.it) [info@lubeteam.it](mailto:info@lubeteam.it)

Italian VAT / C.F. e P.IVA: 01251720627

Follow us



This document is the property of LubeTeam Hydraulic S.r.l. All data reported here are for the exclusive use of the Receiver. Reproduction is not authorized without writing permission, in all or in part of the content of this document, in accordance to Law 633 art. 171, dated April 22, 1941.

Il presente documento è di proprietà della LubeTeam Hydraulic S.r.l. I dati riportati sono per esclusivo del destinatario. La riproduzione, di tutto o in parte, non è autorizzata senza permesso scritto secondo l'art. 171 della L. 633 del 22 Aprile 1941.