



Inserto Stauff
(Tipo ES / EP - Serie Standard)



 HYDRAULIC
COMPONENTS
& FLUID CONTAMINATION
CONTROL





All trademarks belong to their respective owners; third party trademarks, product names, trade names, corporate names and company names mentioned may be trademarks of their respective owners or registered trademarks of other companies and are used for instructional purposes and for the benefit of the owner, without any end of Copyright infringement in force.

Tutti i marchi riportati appartengono ai legittimi proprietari; marchi di terzi, nomi di prodotti, nomi commerciali, nomi corporativi e società citati possono essere di proprietà dei rispettivi titolari o registrati da altre società e sono stati utilizzati a puro scopo esplicativo e a beneficio del possessore, senza alcun fine di violazione dei diritti di Copyright vigenti.

Socket Cap Screw Slotted Head Screw

A



Socket Cap Screw IS

(according to ISO 4762 or ANSI / ASME B18.3)

Dimensions applicable only when used without Cover Plate DP

Slotted Head Screw LI

(according to ISO 1207 or ANSI / ASME B18.6.3)

Dimensions applicable only when used without Cover Plate DP

Ordering Codes

Socket Cap Screw

***IS-*M6x30-*W3**

Slotted Head Screw

***LI-*M6x30-*W3**

* Type of bolt	Socket Cap Screw (according to ISO 4762 or ANSI / ASME B18.3)	IS
	Slotted Head Screw (according to ISO 1207 or ANSI / ASME B18.6.3)	LI

Please note: Socket cap screws IS and slotted head screws LI have to be used in conjunction with washers US, which are available separately.

* Thread type and size acc. to dimension table **M6x30**



* Material code	Carbon Steel, zinc/nickel-plated	W3
	Stainless Steel V2A	W4
	1.4301 / 1.4305 (AISI 304 / 303)	
	Stainless Steel V4A	W5
	1.4401 / 1.4571 (AISI 316 / 316 Ti)	

Group STAUFF	DIN	Dimensions (mm/in) Thread G x L	Ordering Codes (Standard Options)	
			Socket Cap Screws	Slotted Head Screws
1	0	M6 x 20 1/4-20 UNC x 3/4	IS-M6x20-W3 IS-1/4-20UNCx3/4-W3	LI-M6x20-W3 LI-1/4-20UNCx3/4-W3
1A	1	M6 x 20 1/4-20 UNC x 3/4	IS-M6x20-W3 IS-1/4-20UNCx3/4-W3	LI-M6x20-W3 LI-1/4-20UNCx3/4-W3
2	2	M6 x 25 1/4-20 UNC x 1	IS-M6x25-W3 IS-1/4-20UNCx1-W3	LI-M6x25-W3 LI-1/4-20UNCx1-W3
3	3	M6 x 30 1/4-20 UNC x 1-1/8	IS-M6x30-W3 IS-1/4-20UNCx1-1/8-W3	LI-M6x30-W3 LI-1/4-20UNCx1-1/8-W3
4	4	M6 x 35 1/4-20 UNC x 1-3/8	IS-M6x35-W3 IS-1/4-20UNCx1-3/8-W3	LI-M6x35-W3 LI-1/4-20UNCx1-3/8-W3
5	5	M6 x 50 1/4-20 UNC x 2	IS-M6x50-W3 IS-1/4-20UNCx2-W3	LI-M6x50-W3 LI-1/4-20UNCx2-W3
6	6	M6 x 60 1/4-20 UNC x 2-1/2	IS-M6x60-W3 IS-1/4-20UNCx2-1/2-W3	LI-M6x60-W3 LI-1/4-20UNCx2-1/2-W3
7	7	M6 x 90 1/4-20 UNC x 3-3/8	IS-M6x90-W3 IS-1/4-20UNCx3-3/8-W3	ON REQUEST ONLY
8	8	M6 x 110 1/4-20 UNC x 4-3/8	IS-M6x110-W3 IS-1/4-20UNCx4-3/8-W3	ON REQUEST ONLY

All threaded parts are available with Metric ISO thread or unified coarse (UNC) thread according to dimension table. Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Hexagon Head Bolt Type AS

**Insert
Type ES / EP**



Hexagon Head Bolt AS

(according to DIN 931 / 933 or ANSI / ASME B18.2.1.)

Dimensions applicable only when used with Inserts EP / ES

Insert EP (Polypropylene)

Insert ES-W3 (Steel, zinc/nickel-plated)

Insert ES-W5 (Stainless Steel V4A)

Ordering Codes

Hexagon Head Bolt

***AS-*M6x27-*W3**

* Type of bolt	Hexagon Head Bolt (according to DIN 931 / 933 or ANSI / ASME B18.2.1.)	AS
----------------	--	----

* Thread type and size acc. to dimension table **M6x27**

* Material code	Carbon Steel, zinc/nickel-plated	W3
	Stainless Steel V2A	W4
	1.4301 / 1.4305 (AISI 304 / 303)	
	Stainless Steel V4A	W5
	1.4401 / 1.4571 (AISI 316 / 316 Ti)	

Group	Dimensions (mm/in)	Ordering Codes
STAUFF	DIN	Thread G x L (Standard Options)
1	0	M6 x 27 AS-M6x27-W3
1A	1	1/4-20 UNC x 1-1/8 AS-1/4-20UNCx1-1/8-W3
		M6 x 27 AS-M6x27-W3
2	2	1/4-20 UNC x 1-1/8 AS-1/4-20UNCx1-1/8-W3
		M6 x 32 AS-M6x32-W3
3	3	1/4-20 UNC x 1-3/8 AS-1/4-20UNCx1-3/8-W3
		M6 x 35 AS-M6x35-W3
4	4	1/4-20 UNC x 1-3/8 AS-1/4-20UNCx1-3/8-W3
		M6 x 42 AS-M6x42-W3
5	5	1/4-20 UNC x 1-5/8 AS-1/4-20UNCx1-5/8-W3
		M6 x 57 AS-M6x57-W3
6	6	1/4-20 UNC x 2-3/8 AS-1/4-20UNC-2-3/8-W3
		M6 x 65 AS-M6x65-W3
7	7	1/4-20 UNC x 2-3/4 AS-1/4-20UNCx2-3/4-W3
		M6 x 95 AS-M6x95-W3
8	8	1/4-20 UNC x 4 AS-1/4-20UNCx4-W3
		M6 x 118 AS-M6x118-W3
		1/4-20 UNC x 4-3/4 AS-1/4-20UNCx4-3/4-W3

Group		Dimensions (mm/in)				Ordering Codes	
STAUFF	DIN	D1	D2	H ES	H EP	(Standard Options)	
1 to 8	0 to 8	11,8 .46	6,5 .26	7,8 .31	8,6 .34	ES-W3	EP

All threaded parts are available with Metric ISO thread or unified coarse (UNC) thread according to dimension table. Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.



LubeTeam Hydraulic S.r.l.

Administration and Headquarter:

Via Tufara Scautieri, 6

83018 - San Martino Valle Caudina (AV)

Office and Warehouse:

S.S. 7 Appia, Km. 237,00

82011 - Airola BN

ITALY

Tel. +39 0823 950 994

Fax +39 0823 412 546

www.lubeteam.it info@lubeteam.it

Italian VAT / C.F. e P.IVA: 01251720627

Follow us



This document is the property of LubeTeam Hydraulic S.r.l. All data reported here are for the exclusive use of the Receiver. Reproduction is not authorized without writing permission, in all or in part of the content of this document, in accordance to Law 633 art. 171, dated April 22, 1941.

Il presente documento è di proprietà della LubeTeam Hydraulic S.r.l. I dati riportati sono per esclusivo del destinatario. La riproduzione, di tutto o in parte, non è autorizzata senza permesso scritto secondo l'art. 171 della L. 633 del 22 Aprile 1941.