


Tubo in polietilene PE metrico e in pollici
Fluidfit
PE - Tierre

LTH
HYDRAULIC
COMPONENTS
& FLUID CONTAMINATION
CONTROL



All trademarks belong to their respective owners; third party trademarks, product names, trade names, corporate names and company names mentioned may be trademarks of their respective owners or registered trademarks of other companies and are used for instructional purposes and for the benefit of the owner, without any end of Copyright infringement in force.

Tutti i marchi riportati appartengono ai legittimi proprietari; marchi di terzi, nomi di prodotti, nomi commerciali, nomi corporativi e società citati possono essere di proprietà dei rispettivi titolari o registrati da altre società e sono stati utilizzati a puro scopo esplicativo e a beneficio del possessore, senza alcun fine di violazione dei diritti di Copyright vigenti.

Technical Information

PE tubing is made from FDA compliant.
Temperature: -29°C (-20°F) to +66°C (150°F)
Suitable for water purification, water conditioners, ice makers, misting systems and food contact applications.
Suitable for a wide range of temperatures and pressures.
Broad chemical compatibility.

Tubo PE in accordo alla FDA.
Temperatura: -29°C (-20°F) to +66°C (150°F)
Idoneo per depuratori, condizionatori ad acqua, macchine del ghiaccio, nebulizzatori e applicazioni a contatto con alimenti.
Idoneità per un ampio range di temperatura e pressione.
Estesa compatibilità chimica.

Metric tube - tubo metrico

PE



TUBE	Ø O.D.	Ø I.D.	Wall Thickness (mm)	Minimum bending radius at 23°C (mm)	Max Working Pressure (bar)	Working Pressure 20°C (bar)	Working Pressure 65°C (bar)	Burst pressure at 23°C (bar)	Minimum Tensile test (kgf/cm)	(mt.)
PE 0425..FF	4 ±0,08	2,5	0,75 ±0,08	25	16	15	8	30	5	200
PE 0604..FF	6 ±0,08	4	1 ±0,08	25	16	15	8	30	10	100
PE 0806..FF	8 ±0,08	6	1 ±0,08	25	12	10	6	20	15	100
PE 1007..FF	10 ±0,08	7	1,5 ±0,08	32	12	10	6	20	20	100
PE 1209..FF	12 ±0,10	9	1,5 ±0,08	63	12	10	6	20	20	100

ØD	Natural	Black (ACS)	White	Red	Blue (ACS)	Green (NEW)	Yellow (NEW)
4x2,5	PE0425NU-FF	PE0425NE-FF	PE0425BO-FF	PE0425RO-FF	PE0425BL-FF	PE0425VD-FF	PE0425GL-FF
6x4	PE0604NU-FF	PE0604NE-FF	PE0604BO-FF	PE0604RO-FF	PE0604BL-FF	PE0604VD-FF	PE0604GL-FF
8x6	PE0806NU-FF	PE0806NE-FF	PE0806BO-FF	PE0806RO-FF	PE0806BL-FF	PE0806VD-FF	PE0806GL-FF
10x7	PE1007NU-FF	PE1007NE-FF	PE1007BO-FF	PE1007RO-FF	PE1007BL-FF	PE1007VD-FF	PE1007GL-FF
12x9	PE1209NU-FF	PE1209NE-FF	PE1209BO-FF	PE1209RO-FF	PE1209BL-FF	PE1209VD-FF	PE1209GL-FF

Black and blue PE tubes are certified
I tubi PE nero e blu sono certificati

Inch tube - tubo in pollici

PE



TUBE	Ø O.D.	Ø I.D.	Wall Thickness (mm)	Minimum bending radius at 23°C (mm)	Max Working Pressure (PSI)	Working Pressure 20°C (PSI)	Working Pressure 65°C (PSI)	Burst pressure at 23°C (PSI)	Min. Tensile test (kgf/cm)	(mt.)
PE 3/16..FF	3/16 ±0,08	0,125" (3,18)	0,79 ±0,08	1,00" (25,4)	230	217	116	435	5	200
PE 1/4..FF	1/4 ±0,08	0,170" (4,32)	1,02 ±0,08	1,00" (25,4)	230	217	116	435	10	100
PE 5/16..FF	5/16 ±0,08	0,216" (5,49)	1,22 ±0,08	1,13" (28,7)	170	217	116	435	15	100
PE 3/8..FF	3/8 ±0,08	1/4" (6,35)	1,58 ±0,08	1,25" (31,8)	170	217	116	290	20	100
PE 1/2..FF	1/2 ±0,1	3/8" (9,53)	1,58 ±0,08	2,50" (63,5)	170	145	87	290	20	100

For size Ø5/32 tube, please use the Ø04 mm on page 63 - Per il tubo Ø5/32 si consiglia di utilizzare il tubo Ø4 a pag. 63

ØD	Natural	Black (ACS)	White	Red	Blue (ACS)	Green (NEW)	Yellow (NEW)
3/16	PE3/16NU-FF	PE3/16NE-FF	PE3/16BO-FF	PE3/16RO-FF	PE3/16BL-FF	PE3/16VD-FF	PE3/16GL-FF
1/4	PE1/4NU-FF	PE1/4NE-FF	PE1/4BO-FF	PE1/4RO-FF	PE1/4BL-FF	PE1/4VD-FF	PE1/4GL-FF
5/16	PE5/16NU-FF	PE5/16NE-FF	PE5/16BO-FF	PE5/16RO-FF	PE5/16BL-FF	PE5/16VD-FF	PE5/16GL-FF
3/8	PE3/8NU-FF	PE3/8NE-FF	PE3/8BO-FF	PE3/8RO-FF	PE3/8BL-FF	PE3/8VD-FF	PE3/8GL-FF
1/2	PE1/2NU-FF	PE1/2NE-FF	PE1/2BO-FF	PE1/2RO-FF	PE1/2BL-FF	PE1/2VD-FF	PE1/2GL-FF

Black and blue PE tubes are certified
I tubi PE nero e blu sono certificati

LubeTeam Hydraulic S.r.l.
Administration and Headquarter:
Via Tufara Scautieri, 6
83018 - San Martino Valle Caudina (AV)
Office and Warehouse:
S.S. 7 Appia, Km. 237,00
82011 - Airola BN
ITALY

Tel. +39 0823 950 994
Fax +39 0823 412 546

www.lubeteam.it info@lubeteam.it

Italian VAT / C.F. e P.IVA: 01251720627

Follow us



This document is the property of LubeTeam Hydraulic S.r.l. All data reported here are for the exclusive use of the Receiver. Reproduction is not authorized without writing permission, in all or in part of the content of this document, in accordance to Law 633 art. 171, dated April 22, 1941.

Il presente documento è di proprietà della LubeTeam Hydraulic S.r.l. I dati riportati sono per esclusivo del destinatario. La riproduzione, di tutto o in parte, non è autorizzata senza permesso scritto secondo l' art. 171 della L. 633 del 22 Aprile 1941.